Form	9-331	
Dag	1072	

APPROVED BY ________CONDITIONS OF APPROVAL, IF ANY:

	Form Approved.		
•	Budget Bureau No. 42-R1424		

UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	LC-067858		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT I Empire Abo Pre Project	NAME ssureMaintenance	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME RECEIVE		
1. oil TA gas well other	Empire Abo Uni 9. WELL NO.		
2. NAME OF OPERATOR ARCO Cil and Gas Company Division of Atlantic Richfield Company	14 10. FIELD OR WILDCAT	FEB 6 198	
3. ADDRESS OF OPERATOR	Empire Abo	O. C. D.	
Box 1710, Hobbs, New Mexico 88240	11. SEC., T., R., M., OR BLK. AND SURVEY TO A. OFFICE		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FNL & 1980' FWL, Unit 1tr C	11–18S–27E		
AT SURFACE:	12. COUNTY OR PARISH	1 13. STATE	
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: as above	Eddy	N.M.	
00 000,0	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 FLEVATIONS (OLIO	W. D. T. (1971)	
	15. ELEVATIONS (SHOW 3573' GR	V DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<u> </u>		
TEST WATER SHUT-OFF	EIVED		
REPAIR WELL	(NOTE: Report results of m change on Form 9	nultiple completion or zone	
MULTIPLE COMPLETE JAN	1 5 1980	-330.)	
CHANGE ZONES			
ABANDON* (other) ABTECIA	OGICAL SURVEY		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	NEW MEXICO	Laive partinent dates	
including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinen	irectionally drilled give sul	bsurface locations and	
Propose to plug & abandon a temporarily abandon	ed well in the Emp	oire Abo Pressure	
Maintenance Project in the following manner:			
 Rig up, kill well, install BOP. RIH w/5½" cmt retr, set @ 3925', squeeze cmt 	holor moter == 11.75	GT C1 C	
4% gel, \(\frac{1}{4}\) flocele/sk, 2% CaCl. Spot heavy 1	hrine del mud heta	sx CI C cmt cont g	
3. Spot approx 15 sx C1 C cmt cont'g 2% CaCl (10	00' plug) 853-953'	inside 5½" csg.	
4. Spot 10 sx C1 C cmt @ surf, install regulation	on dry hole marker	c, clean & level	
location.			
	•		

Subsurface Safety Valve: Manu. and Type	Set	@Ft.	
18. I hereby certify that the foregoing is true and correct			
SIGNED TITLE Dist. Drlg. St	upt. DATE 1/11/8	30	
(This space for Federal or State office	<u> </u>		
Unis space for Federal or State office	ce use)		