Form 9-831 a (Feb. 1951)

(SUBMIT IN TRIPLICATE) UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

JAN 1 1 1963

SUNDRY NOTICES AND REPORTS ON WELLS C. C. ARTESIA, OFFICE

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
--	--

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

1 - 1		November 16 , 19 52
رُّنَ (' Well No. <u>1</u> is	located 330 ft. from line and 3	30 ft. from $\left\{ \begin{array}{l} \mathbf{E} \\ \mathbf{W} \end{array} \right\}$ line of sec. 12
(½ Sec. and Sec. No.) Engli : 3 Abo (Field)	188 278 (Twp.) (Range) Rddy (County or Subdivision)	(Meridian) Key Hexico (State or Territory)

The elevation of the derrick floor above sea level is 3620 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The above well was plugged and abandoned in the following manner.

- 1. Loaded hole with mud ladden fluid.
- 2. Set 35 sack cement plug over perforations at 6128-38' and 6154-64'.
- 3. Cut off 52" cag at 4100' and pulled same. Set 35 sack cement plugs as follows: 3500' (Yeso), 2400' (San Andres), and in and out of 8-5/8" csg at 1492' .
- Set a 5 sack cement plug at surface.
- Set marker, cleared and leveled location and filled pit to ment specialisations.

orginial signed by:
LESTER L. DUKE
·
e District Superintendent
•