(Do not

TEST WATER SHUT-OFF

STATES SUBMIT IN TALLYLICATES THE INTERIOR (Other instructions on re-

Form approved. Budget Bureau No. 42-R1424 5. LEASE DESIGNATION AND SERIAL NO.

REPAIRING WELL

SUBSEQUENT REPORT OF:

1 /	: 171 L Y		! ! L	11417	י חטוו	verse side))
	GEOLO	OGICAL.	su	RVEVI	l Cons	. Com	ISSION

GEOLOGICAL SURVEY DO COMMISSION	NM 42410
SUNDRY NOTICES AND REPORTS 10 NINVESS 10	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	
CAS	7. UNIT AGREEMENT NAME

	ose Attition for Firmit— for such proposals.)			
1.	WELL X GAS WELL OTHER re-entry	7. UNIT AGREEMENT NAME		
2.	Fred Pool Drilling, Inc.	8. FARM OR LEASE NAME		
3.	ADDRESS OF OPERATOR	WhiteOak Federal 9. WELL NO.		
1.	P.O.Box 1393 Roswell, N.M. 88201 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface RECEIVED BY 2310 FSL 2355 FEL NW/4 SE/4 JAN 27 1986	2 10. FIELD AND POOL, OR WILDCAT Artesia Oil Pool 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12-18S-27E		
14.	PERMIT NO. 15. BLEVATIONS (Show whether DF, RT, GR, etc.). C. D. 3617 Gr ARTESIA, OFFICE	12. COUNTY OF PARISH 13. STATE Eddy NM		
lG.	Check Appropriate Box To Indicate Harure of Notice, Report, or O	ther Data		
	NOTICE OF INTENTION TO:	SURSTANTANT REPORT OF		

FRACTURE TREAT FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING ABANDONMENT* REPAIR WELL surface cement CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Jan. 14,1986: Cleaned out hole to 380 ft. Ran 368 ft.

of new 24# 8 5/8 casing. Spotted 25 sx plug at 380 ft. Cemented with 300 sx Class

WATER SHUT-OFF

C,2% CaCl, \%# floseal per sx.

Ran temperature survey; top of cement at

350 ft.

PULL OR ALTER CASING

MULTIPLE COMPLETE

Jan. 15,1986:

Spotted 25 sx plug thru 1". Tagged at 322 ft. Spotted 50 sx plug thru 1", tagged at 322 ft. Spotted 50 sx plug thru 1", tagged at 275 ft.

Jan. 16,1986: Spotted 50 sx plug thru 1", tagged at 232 ft.

Circulated cement to surface with 275 sx of

Class C,2% CaCl, \tau# floseal per sx.

W 0 C 24hrs.

Jan.18,1986: Commenced cleaning out well.

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE _	Vice	President	DATE 1-20-86
(This space for Federal or State office use)				
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE			DATE

JAN 24 1986

*See Instructions on Reverse Side