
NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL



Titre

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of report by checking below:	
	of report by checking below:
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
EPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
EPORT ON RESULT OF PLUGGING OF WELL	K
OIL CONSERVATION COMMISSION anta Fe, New Mexico.	Artesia, N. M. 3/7/45
ollowing is a report on the work done and the resu	elts obtained under the heading noted above at the
Dale Resler Company or Operator	Jones State Well No. 1 in the
	T185, R. 27E, N. M. P. M.,
	Eddy County
Plug wa s r un from botto	ORK DONE AND RESULTS OBTAINED but not re- received to dat om of hole, with mud and gravel to
Plug was run from botto 1860', inserted cement bridg 1860 to 1475', inserted cement plugged back to 400' with mucement. 350' 8" pulled. Mu	received to date of hole, with mud and gravel to ge with five sacks cement; mud from ent bridge with five sacks cement; and, inserted bridge with five dacks added to surface, setting 4' monument.
Plug was run from botto 1860', inserted cement bridg 1860 to 1475', inserted cement plugged back to 400' with mu cement. 350' 8" pulled. Mu	received to date of hole, with mud and gravel to ge with five sacks cement; mud from ent bridge with five sacks cement; and, inserted bridge with five dacks added to surface, setting 4' monument.
Plug was run from botto 1860', inserted cement bridg 1860 to 1475', inserted cement plugged back to 400' with mucement. 350' 8" pulled. Mu	received to date of hole, with mud and gravel to ge with five sacks cement; mud from ent bridge with five sacks cement; and, inserted bridge with five dacks added to surface, setting 4' monument.

Alexandra de la capacitación de la capacita del capacita del capacita de la capacita del capacita de la capacita de la capacita del capacita de la capacita de la capacita de la capacita de la capacita del capacita de la capacita del capacita de la capacita del cap

e die de Withe 24**A** Se**du Redu**nction de la compa