

NEW MEXICO OIL CONSERVATION COMMISSION

Grid for well location mapping.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, its proper agent, not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Company or Operator: Dale Resler
Address: P. O. Box 464, Artesia, New Mexico
State: Well No. 3 of Sec. 13, T. 18S, R. 27E, N. M. P. M., Artesia Field, Eddy County.
Well is 990 feet south of the North line and 1680 feet west of the East line of Section 3.
If State land the oil and gas lease is No. B-9965 Assignment No. 1.
If patented land the owner is Address.
If Government land the permittee is Address.
The Lessee is Roy G. Barton Address.
Drilling commenced 1-29-45 Drilling was completed 2-22-45.
Name of drilling contractor S. P. Yates Address: Artesia, New Mexico.
Elevation above sea level at top of casing feet.
The information given is to be kept confidential until.

OIL SANDS OR ZONES

No. 1, from 1510 to 1530 No. 4, from
No. 2, from 1892 to 1896 No. 5, from
No. 3, from to No. 6, from

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 345 to 347 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10 7/8	8"	350'				25
8"	7"	1750'	50			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 2047 feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

S. W. Grimes Driller
Jim Miller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this day of 19
Notary Public
Place Date
Name
Position
Representing
Company or Operator
Address

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	80	80	Red Rock & Gyp
80	170	90	Broken Red Rock, gyp and Shale
170	200	30	Anhy
200	270	70	Anhy
270	285	15	Water Sand
285	290	5	Water Sand
290	340	50	Anhy & Anhy & Red Rock
340	347	7	Water Sand
347	355	8	Anhy
355	370	15	Anhy
370	375	5	Red Rock
375	440	65	Anhy
440	495	55	Anhy
495	535	40	Anhy
535	590	55	Anhy
590	640	50	Anhy
640	650	10	Anhy & Grey Lime
650	975	325	Anhy
975	980	5	Red Bed
980	1020	40	Anhy & Red Rock
1020	1060	40	Anhy
1060	1095	35	Anhy
1095	1145	50	Anhy & Red Rock
1145	1195	50	Anhy
1195	1212	17	Anhy
1212	1232	20	Red Sand
1232	1250	18	Red Sand
1250	1310	60	Broken Anhy
1310	1365	55	Anhy
1365	1415	50	Anhy
1415	1475	60	Anhy
1475	1500	25	Broken Anhy
1500	1510	10	Anhy and Black Sand
1510	1530	20	Sand Show oil
1530	1550	20	Sandy Shale
1550	1630	80	Broken Anhy
1630	1700	70	Broken Lime
1700	1740	40	Lime
1740	1765	25	Grey Lime
1765	1880	115	Lime
1880	1892	12	Hard Lime
1892	1896	4	Brown Lime Show of oil
1896	1900	4	Lime
1900	1915	15	Sandy Lime
1915	2000	85	Lime
2000	2025	25	Broken Lime and red sand
2025	2047	22	lime
2047			