

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>EULF OIL CORP.</u>		Lease <u>EDDY STATE "BU"</u>		Well # <u>I</u>	
Location of Well	Unit <u>J</u>	Section <u>16</u>	Township <u>18</u>	Range <u>27</u>	County <u>EDDY</u>
Drilling Contractor	<u>RIG # 4</u> <u>LEE DRG. CO.</u>		Type of Equipment <u>ROTARY</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11"</u>	<u>8 5/8"</u>	<u>24 #</u>	<u>NEW</u>	<u>1550</u>	<u>380</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>9.5 #</u>	<u>NEW</u>	<u>6000</u>	<u>200</u>

Casing Data:

Surface 52 joints of 8 5/8 inch 24 # Grade J.S. API New

Pipe (Approved) (Rejected)

Inspected by LOBLEY date 11-29-61

Cementing Program

Size of hole 11 Size of Casing 8 5/8 Sacks cement required 346 + 1290

Type of Shoe used GUIDE Float collar used YES Btm 3 jts welded Yes

TD of hole 1503 Set 1479 Feet of 8 5/8 Inch 24 # Grade J.S. API

New-used csg. @ with 650 sacks neat cement around shoe + casing

+ 650 additives New

Plug down @ 5:40 (AM) (PM) Date 12-1-61

Cement circulated NO * No. of Sacks

Cemented by B-T Cementing Co. Witnessed by LOBLEY

Temp. Survey ran @ (AM) (PM) Date 12-1-61 top cement @ 138

Casing test @ (AM) (PM) Date

Method Used Witnessed by LOBLEY

Checked for shut off @ 3:00 (AM) (PM) Date 12-2-61

Method used 600 # press Witnessed by L. L. L.

Remarks: Two plugs used.

* For cement tags at 138'. Circulation was completed by pumping in 50 additional sks. of cement through tubing on outside of casing.

1493
2211
1495
1496
4492
2996
3001878