

	X		

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LAND OFFICE State #B-3635

LEASE NO. Lease Unitized

UNIT "C"

RECEIVED

APR 22 1960

SUNDRY NOTICES AND REPORTS ON WELLS - B. C.

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL UP ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Abo Chalk Bluff Draw Unit

April 20, 1960

WELL NO. 6 IS LOCATED 660 FT. FROM N LINE AND 1980 FT. FROM W LINE OF SEC. 16
NE/4 of NW/4 18-S 27-E N 1/2 PM
(1/4 SEC. AND SEC. NO.) (TWP.) (RANGE) (MERIDIAN)
Empire Abo Eddy New Mexico
(FIELD) (COUNTY OR SUBDIVISION) (STATE OR TERRITORY)

THE ELEVATION OF THE DERRICK FLOOR ABOVE SEA LEVEL IS 3495 FT.

DETAILS OF WORK

(STATE NAMES OF AND EXPECTED DEPTHS TO OBJECTIVE SANDS, SHOW SIZES, WEIGHTS, AND LENGTHS OF PROPOSED CASINGS; INDICATE MUDDING JOBS, CEMENTING POINTS, AND ALL OTHER IMPORTANT PROPOSED WORK.)

Set 5669.42' of 4-1/2", J=55, 9.5# csg. (140 jts.) at 5680'. Cement with 800 sacks 12% gel. cement. POB 9:10 p.m. 4-16-60. Top of cement at 800' outside 4-1/2" csg. (oil string) by temperature survey (McCullough). Tested 4-1/2" csg. with 1500# for 30 min. = no drop in pressure. Acidized perforations from 5568-5582', 5602-5616' with 10,000 gallons regular 15% acid, averaging rate 6 BPM.

John L. G. G. G.

I UNDERSTAND THAT THIS PLAN OF WORK MUST RECEIVE APPROVAL IN WRITING BY THE GEOLOGICAL SURVEY BEFORE OPERATIONS MAY BE COMMENCED

COMPANY Humble Oil & Refining Company

ADDRESS _____

ORIGINAL
SIGNED:

R. R. ALWORTH

By _____

TITLE Agent