

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

1503
2311
1523
1503
4509
2311
433

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>PAN-AM. PET. CORP.</u>		Lease <u>STATE "CE"</u>		Well # <u>1</u>	
Location of Well	Unit <u>H</u>	Section <u>16</u>	Township <u>18</u>	Range <u>27</u>	County <u>EDDY</u>
Drilling Contractor <u>LFE DRILLING CO.</u>	Type of Equipment <u>ROTARY</u>				

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
11"	8 5/8"	24 #	NEW	1500	CIRC.
7 7/8"	4 1/2"	9.5 #	NEW	6100	TIE IN TO SURF.

Casing Data:

Surface 47 joints of 8 5/8 inch 24 # Grade J.E. API. New
Low High (Approved) (Rejected)

Inspected by LOBLEY date 7-10-61

Cementing Program

Size of hole 11 Size of Casing 8 5/8 Sacks cement required 347

Type of Shoe used GUIDE Float collar used YES Btm 3 jts welded THRED-LOCK

TD of hole 1515 Set 1503 Feet of 8 5/8 inch 24 # Grade J.E. API.

New used csg. @ 100 with 100 sacks neat cement around shoe
+ 600 sax INCR additives 290 GEK

Plug down @ 6100 (AM) (PM) Date 7-10-61

Cement circulated YES No. of Sacks 200

Cemented by HALLIBURTON Witnessed by LOBLEY

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ 6100 (PM) Date 7-12-61

Method used 60/6645 # 30" Witnessed by R. L. Lolley

Remarks:

2.22. up well case 6100 ft.