

NEW MEXICO OIL CONSERVATION COMMISSION

DRAWER DD

ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>HUMBLE OIL & REF. CO.</u>		Lease <u>ABC CHALK BLUFF DRAW</u>		Well # <u>26</u>	
Location of Well	Unit <u>R</u>	Section <u>17</u>	Township <u>18^S</u>	Range <u>27^E</u>	County <u>EDDY</u>
Drilling Contractor	<u>LEE DRILLING CO</u>		Type of Equipment <u>ROTARY</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11</u>	<u>8 5/8</u>	<u>24</u>	<u>NEW</u>	<u>1500</u>	<u>CIRC.</u>
	<u>4 1/2</u>	<u>9.5</u>	<u>NEW</u>	<u>6000</u>	<u>TIE 8 5/8</u>
Casing Data:					
<u>XP</u> Surface <u>45</u> joints of <u>5 7/8</u> inch <u>24</u> # Grade <u>J. S. S. A.P.I.</u>					
(Approved) (Rejected) <u>NO</u> <u>C.I.A.I.</u>					
Inspected by <u>J. H. B.</u> date <u>7-20-61</u>					
Cementing Program					
Size of hole <u>11</u> Size of Casing <u>5 7/8</u> Sacks cement required <u>347</u>					
Type of Shoe used <u>14</u> Float collar used <u>15</u> Btm 3 jts welded <u>1000-000</u>					
<u>XP</u> TD of hole <u>150</u> Set <u>1000</u> Feet of <u>5 7/8</u> inch <u>24</u> # Grade <u>J. S. S. A</u>					
New-used csg. @ <u>750</u> with <u>550</u> sacks neat cement around shoe					
+ <u>250</u> sack <u>750</u> additives <u>20</u> <u>100</u> <u>100</u>					
Plug down @ <u>1:15</u> (AM) (PM) Date <u>7-24-61</u>					
Cement circulated <u>TRACE</u> * No. of Sacks					
Cemented by <u>HALLIDAY</u> Witnessed by <u>L. P. H. I.</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ <u>4:10</u> (AM) (PM) Date <u>7-24</u>					
Method used <u>150</u> <u>100</u> <u>100</u> Witnessed by <u>20</u> <u>100</u>					
Remarks: <u>* 1" being run, 2 1/2' and circulation completed</u>					
<u>Wj of pump, in an additional 150 sacks.</u>					

1500 to
2411

1500 to

1500 to

1500 to

1500 to

P. H. B. 61