

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Bob</u>		Lease <u>100</u>		Well # <u>1</u>	
Location of Well	Unit <u>N</u>	Section <u>19</u>	Township <u>19</u>	Range <u>10</u>	County <u>San Juan</u>
Drilling Contractor <u>Bob</u>	Type of Equipment <u>6</u>				
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
Casing Data:					
Surface <u> </u> joints of <u> </u> inch <u> </u> # Grade <u> </u>					
(Approved) (Rejected) <u> </u>					
Inspected by <u> </u> date <u> </u>					
Cementing Program					
Size of hole <u> </u> Size of Casing <u> </u> Sacks cement required <u> </u>					
Type of Shoe used <u> </u> Float collar used <u> </u> Btm 3 jts welded <u> </u>					
TD of hole <u> </u> Set <u> </u> Feet of <u> </u> Inch <u> </u> # Grade <u> </u>					
New-used csg. @ <u> </u> with <u> </u> sacks neat cement around shoe					
+ <u> </u> sax <u> </u> additives <u> </u>					
Plug down @ <u> </u> (AM) (PM) Date <u> </u>					
Cement circulated <u> </u> No. of Sacks <u> </u>					
Cemented by <u> </u> Witnessed by <u> </u>					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u>1- 5:12 PM</u>					

1- 1 3/4" ID to 5' 2- 1 1/2" ID to 10'

1- 1 1/2" ID to 10' 2- 1 1/2" ID to 10'

1- 1 1/2" ID to 10' 2- 1 1/2" ID to 10'