

N. M. O. C. C. COPY

RECEIVED

MAR 3 0 1961

SUNDRY NOTICES AND REPORTS ON WELLS D. C. C. ARTESIA, DEFIN	
Price of milatrica to couls	
PTICE OF INTENTION TO CHANGE PLANS PTICE OF INTENTION TO TEST WAYER SHATLOFF	SUBSECUTOR REPORT OF SUBSTRIES OR ACCORDING
MICE OF INTENTION TO RE-SHILL OR REPAIR WELL	
STICE OF INTENTION TO SHOOT ON ACIDIES	Supersonate of Assessment
STICE OF INFESTION TO ADARDON WOLL	
(INDICATE AGOVE OV CHECK MAR	IN NATURE OF REPORT, NOTICE, OR OTHER GATE)
	July 27
ideral Hearburg II No. 2-32 is located 230 ft. free	m_ N line and 2278.4 ft. from E line of sec32
	78 N.M.P.M.
(fup.)	(Rings) (Mintaling)
et Royton Undesignated (County	Midy Maries (Out or Turbury)
2224	
s test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe.	tubing, setting approximately 1310° - 950°. 'tubing, setting approximately 150° - 100°. 'tubing, setting approximately 150° - 100°. 'Ar surface and set 5 seck plug with marker
s test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. k was witnessed by a representati	tubing, setting approximately 1310° - 950°.
s test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. k was witnessed by a representati	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. Ar surface and set 5 seek plug with marker we of the State Engineer's office and was RECEIVED
s test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. k was witnessed by a representati	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. ar surface and set 5 seek plug with marker we of the State Engineer's effice and was RECEIVED OCT 2 8 1960
is test was plugged as follows: 1. Pusped 85 sack plug thru 2" 2. Pusped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. It was witnessed by a representation	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. ar surface and set 5 seek plug with marker we of the State Engineer's effice and was RECEIVED OCT 2 8 1960
is test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. k was witnessed by a representation pleted 2:00 P.M. July 9, 1960.	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. 'ar surface and set 5 seek plug with marker we of the State Engineer's office and was RECEIVED OCT 2 8 1960 U. S. GEOLOGICAL SURVE
is test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. k was witnessed by a representation pleted 2:00 P.H. July 9, 1960.	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. 'ar surface and set 5 seek plug with marker we of the State Engineer's office and was RECEIVED OCT 2 8 1960 U. S. GEOLOGICAL SURVE
is test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. It was witnessed by a representation ploted 2:00 P.M. July 9, 1960.	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. 'ar surface and set 5 seek plug with merhor we of the State Engineer's office and was RECEIVED OCT 2 8 1960 U. S. GEOLOGICAL SURVE
s test was plugged as follows: 1. Pumped 85 sack plug thru 2" 2. Pumped 10 sack plug thru 2" 3. Bridged in 8 5/8" easing no pipe. k was witnessed by a representation placed 2:00 P.H. July 9, 1960.	tubing, setting approximately 1310' - 950'. 'tubing, setting approximately 150' - 100'. 'ar surface and set 5 seek plug with merhor we of the State Engineer's office and was RECEIVED OCT 2 8 1960 U. S. GEOLOGICAL SURVE