POPM - 3881 a C Feb. 1951) S 2 NOV 5 162 NOV 5 162 NOV FRONNIE E. SHOOK ER ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES HOOK ENGINEER DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

B ₁			reau covec La	1.				
Land		C e	05					
Unit				P				
	R	E	C	E	1	V	300	

NOV 6 1962

SUNDRY NOTICES AND REPORTS ON WELLS. G. C.

 	ARIESISCULING
	SUBSEQUENT REPORT OF WATER SHUT-OFF
 1	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

		Makembar T. Time	19
Well No. 35 is located	900 ft. from NN line a	and $\frac{2310}{\text{ft. from}}$ line of so	8 ec
SW/NE/NE Section 8	18-5, 27-5	H.M.P.M.	
(½ Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)	
The elevation of the derrick flo	(County or Subdivision) 344(or above sea level is	(State or Territory) Oft.	

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

drilling at approximately 2,000 feet and would like permission to drill to approximately 2800 feet to test the top of the Glorietta formation. Before running any pipe, we will discuss our pipe and cementing program with you.

I understand that this plan of work must receive approval in writing by the Geological Survey belties operations may be eduling the Geological Survey belties operations and Geologic