

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.**

AREA 640 ACRES
LOCATE WELL CORRECTLY

V. S. Welch

Artesia, New Mexico

Three Sands-State Company or Operator
Lease 28 Well No. 8 in NWSE of Sec. 17, T. 18
R. 28, N. M. P. M., Artesia Field, Eddy County.
Well is 3560 feet south of the North line and 1730 feet west of the East line of 17-18-28
If State land the oil and gas lease is No. 647 Assignment No. _____
If patented land the owner is _____, Address _____
If Government land the permittee is _____, Address _____
The Lessee is _____, Address _____
Drilling commenced July 9, 1953 Drilling was completed August 29, 1953
Name of drilling contractor V. S. Welch Address Artesia, N. M.
Elevation above sea level at top of casing _____ feet.
The information given is to be kept confidential until _____ 19____.

No. 1, from.....to..... №. 4, from.....to.....
 No. 2, from.....to..... №. 5, from.....to.....
 No. 3, from.....to..... №. 6, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

[illegible]

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
				Well Plugged		

Heaving plug—Material..... Length..... Depth Set.....
Adapters — Material..... Size.....

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment.....

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from **0** feet to **2580** feet, and from _____ feet to _____ feet.

Put to producing.....**Dry Hole**....., 19.....

The production of the first 24 hours was.....barrels of fluid of which.....% was oil;% emulsion;% water; and.....% sediment. Gravity, Be.....

If gas well, cu. ft. per 24 hours.....Gallons gasoline per 1,000 cu. ft. of gas.....

Rock pressure, lbs. per sq. in.....

..... **J. M. Welch**, Driller Driller
..... **C. H. Parker**, Driller Driller

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 26th
day of October, 1953
Glenn Foster
Notary Public

Artesia, N. M. 10-26-53
Place Date
Name L. J. Melick
Position Agent
Representing H. S. Walsh

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	25		Gyp.
25	260		Red Sand
260	275		Anhy
275	290		Shale
290	315		RR & Sand
315	335		Red Shale
335	345		Anhy
345	350		Gumbo
350	355		Gyp
355	375		Shale
375	445		R.R. Sandy
445	490		R.R. & Anhy
490	500		Anhy
500	507		Blue Shale
507	515		Anhy
515	519		Red Rock
519	523		Anhy
523	526		Lime
526	532		Sand
532	536		Anhy
536	539		R.R.
539	580		Anhy
580	620		Anhy & Lime
620	630		Lime
630	675		Anhy & Lime
675	725		Sandy R.R.
725	760		Anhy
760	775		Red Bed
775	830		Anhy & R.R. Bkn.
830	975		Anhy & R.R.
975	1310		Anhy
1310	1340		Anhy & Red Sand Bkn.
1340	1475		Anhy
1475	1525		Anhy & R.R. Bkn.
1525	1580		Anhy
1580	1600		Red Sand
1600	1610		Anhy
1610	1690		Anhy & Red Sdy. R.R.
1690	1735		Anhy
1735	1750		Pink Lime
1750	1765		Red Sand & Shale
1765	1795		Anhy & Lime
1795	1807		Anhy shells & Red Sand
1807	1817		Red Sand
1817	1825		Gray Sdy. Lime
1825	1855		Red Sand
1855	1885		Red Sand, Gyp & Sdy. shells
1885	1920		Gray Lime, bkn. shale
1920	1930		Lime
1930	1940		Hard Gray Lime
1940	2000		Lime
2000	2008		Gray Lime
2008	2015		Sdy. Pink Lime
2015	2020		Gray Lime
2020	2045		Lime & Sand
2045	2052		Gray Sand
2052	2065		Gray Lime
2065	2162		Lime
2162	2175		B. Lime
2175	2194		Lime, sdy.
2194	2240		Lime
2240	2245		Sdy. Lime
2245	2275		Lime
2275	2284		Pink Lime
2284	2304		Lime
2304	2330		Pink Lime
2330	2340		Sdy. Lime
2340	2399		White Lime
2399	2413		Gray Lime
2413	2429		White Lime
2429	2442		Lime
2442	2447		Bkn. Lime
2447	2454		B. Lime
2454	2470		Lime
2470	2485		Gray Lime
2485	2491		Lime
2491	2502		Gray Lime
2502	2505		Hard White Lime
2505	2553		Lime
2553	2567		Hard Lime
2567	2580		Lime