


N

0									

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Earl Ployhar,Artesia, New Mexico

Company or OperatorAddress

StateWell No. 1 in NW NW of Sec. 3, T. 18S

Lease

R. 28E, N. M. P. M., Artesia Field, Eddy County.

Well is 330 feet south of the North line and 330 feet east of the West line of Section 3

3-6043

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Earl Ployhar Address Artesia

Drilling commenced January 23 19 41 Drilling was completed April 3 19 41

Name of drilling contractor E.J.Anderson & H. A. Dewey Address Artesia, N. M.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 890 to 900	No. 4, from to
No. 2, from 2180 to 2190	No. 5, from to
No. 3, from 2230 to 2252	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 290 to 300	feet.
No. 2, from 2180 to 2190	feet.
No. 3, from 2230 to 2252	feet.
No. 4, from to	feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 1/2	28			507	Std				
7"	20			2152	"				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 1/2	507	50 sx			
8 1/2"	7"	2152	100 "			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	50		Caliche
50	230		Red Rock
230	290		Anhydrite
290	300		Water Sand
300	305		Red Beds
305	330		Anhydrite
330	340		Red Rock
390	415		Red Bed
415	430		Gyp
430	465		Anhydrite
465	495		Gyp & Red Beds
495	543		Anhydrite
543	545		Blue Shale
545	600		Anhydrite
600	625		Red Sandy Shale
625	650		Anhydrite
650	660		Red Beds
660	720		Anhydrite
720	725		Red Beds
725	890		Anhydrite
890	900		Gray Lime - OIL SHOW
900	1370		Anhydrite
1370	1450		Anhydrite & Red Shale Stringers
1450	1470		Red Sand
1470	1480		Sandy Shale
1480	1495		Anhydrite
1495	1515		Lime & Anhydrite
1515	1525		Anhydrite & Red Rock
1525	1600		Anhydrite & Lime
1600	1620		Anhydrite
1620	1645		Gray Lime
1645	1660		Red Sand - GAS SHOW
1660	1695		Anhydrite
1695	1765		Anhydrite & Lime
1765	1775		Sandy Lime
1775	1800		Anhydrite
1800	1850		Anhydrite & Sandy Lime
1850	1860		Anhydrite
1860	1875		Anhydrite & Red Shale
1875	1895		Anhydrite & Lime
1895	1915		Red Sandy Shale & Anhydrite
1915	1940		Brown Sandy Shale & Anhydrite
1940	1960		Lime
1960	2015		Gray Lime
2015	2230		Lime - OIL SHOW 2180-2190
2230	2235		Sandy Lime (CORRECTED SLM TO 2236) - OIL
2235	2252		OIL SAND