



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. 028772 (2)  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

|                                                |                                     |                                            |  |
|------------------------------------------------|-------------------------------------|--------------------------------------------|--|
| NOTICE OF INTENTION TO DRILL                   | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF        |  |
| NOTICE OF INTENTION TO CHANGE PLANS            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     |                                     | SUBSEQUENT REPORT OF ALTERING CASING       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL |                                     | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        |                                     | SUBSEQUENT REPORT OF ABANDONMENT           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    |                                     | SUPPLEMENTARY WELL HISTORY                 |  |
| NOTICE OF INTENTION TO ABANDON WELL            |                                     |                                            |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 8, 1956, 19\_\_

Well No. 19 is located 1900 ft. from [N] line and 1900 ft. from [E] line of sec. 20

SH ML 10 (1/4 Sec. and Sec. No.) 119 (Twp.) 28E (Range) M M P M (Meridian)  
Artesia (Field) 1800 (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Plan to drill to approximately 2600'. Will complete in Grayburg and Livingston sands. Will set 7" surface pipe from 350' to 500' which is below salt. Then will set 4 1/2" at total depth or just above latest pay. Will mud-oil each possible pay zone and complete. Both casing strings will be adequately cemented.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Feeler & Yates et al

Address 304 Carper Building

Artesia, N.M.

By Walter J. Shelton

Title \_\_\_\_\_