

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

Date November 21, 1952 Title Sec. of Oper. Comm.
The summary on this page is for the condition of the well at above date.

Commenced drilling Sept. 17, 1952 Finished drilling Nov. 18, 1952

OIL OR GAS SANDS OR ZONES
(Denote gas by G)

No. 1, from 2572 to 2602 No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
7	2260	100	Halliburton		50

PLUGS AND ADAPTERS

Heaving plug—Material ----- Length ----- Depth set -----
Adapters—Material ----- Size -----

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
2250	Hydra-fuc		2250	11-17	2572-2602	

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Nov. 24	Put to producing	Nov. 19
The production for the first 24 hours was	barrels of fluid of which	% was oil;
emulsion; % water; and % sediment.	Gravity, °Bé.	
If gas well, cu. ft. per 24 hours	Gallons gasoline per 1,000 cu. ft. of gas	
Rock pressure, lbs. per sq. in.		

EMPLOYEES

Frank Sloan	Driller		Driller
	Driller		Driller

FORMATION RECORD

FORMATION RECORD			
FROM—	TO—	TOTAL FEET	FORMATION
25	425		Red Rock
425	500		Anhy.
500	705		Salt
705	1265		Anhy.
1265	1286		Lime
1286	1300		Anhy.
1300	1615		Anhy. & Lime
1615	1842		Anhy.
1842	1875		Red Sand
1875	1997		Anhy.
1997	2010		Lime
2010	2170		Anhy.
2170	2408		Lime
2408	2430		Sandy Lime
2430	2540		Lime
2540	2575		Sandy Lime
2575	2602		Sand
2602	2642		Lime

