



County Eddy Depth 2550' Pool Artesia

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company Franklin, Aston & Fair Well No. 9 Lease State-14

990' Feet from S. Line 660' Feet from W. Line Sec. 14 Twp. 18S Rge. 28E

Land State Contractor A. J. Smith Drlg. Co.*

T. A
T. X 430
B. X 630
T. Del. Li.
T. Del. Sd.
T. Y
T. SR
T. Q
T. GB
T. SA 2522 spl.
T. Glo.
T. Blby
T. CF

CSG. & CEMENTING REC'D

Size	Feet	Sax Cement
<u>8 3/4</u>	<u>450</u>	<u>50</u> ✓
<u>7</u>	<u>2480</u>	<u>100</u> ✓

Elevation 3577 ^{OF} Spudded 10-25-54 Completed 12-18-54

T. Tu. Total Depth 2525 ^{li} P. B.
T. Full Top Pay 2217 District 7
T. DR I. P. F 276 BOPD
T. Wich. Alb. Base on 115 BO 10 Hrs.
T. Abo Choke: open Inch
T. WC Tubing 2 @ 2403 Ft.
T. Hu. Pressures: Tubing 51 Casing 575
T. Per-Pe GOR Gravity 35
T. Penn Effective Perforations
T. Strawn 30h 2217-27
T. Miss. 30h 2275-85
T. WF

T. Dev. Acid & Shooting Record:
T. Fuss. 10,000 gal. acid From 2217 To 27
T. Sil. From 2275 To 85
T. Mon. 10,000 gal. acid From on 2480 To 2525
T. Simp. From To

T. McK
T. Ell.
T. G.W.
T. Gr. SHOWS
T. S/FRESH WATER @ 290' ROSE 40'
T. S/O 2222-27 5g PH
T. S/O 2501-11 100g 24'
T. S/
T. S/
T. S/

October 27, 1954 Drlg. 125' R.B.

<u>3</u>	<u>d 755 antry</u>	<u>DEC 8</u>	<u>prep d plug</u>
<u>VGV 10</u>	<u>d 1552 ✓</u>		<u>TD 2525', 60</u>
	<u>d 2155 li</u>		<u>attemp. sdfrac</u>
	<u>d 2387 ✓</u>		<u>10000 gal. form.</u>
	<u>TP 2525 ✓</u>	<u>DEC 15</u>	<u>wouldnt take</u>
	<u>P.B 2480</u>		<u>TD 2525' li, drlg.</u>
			<u>plug, sdfrac, 10000/</u>

2480-2525, Dr. Plug @ 2326, perf.

30/2275-85, Soil fac/10000/2275-

85, Set Br. plug @ 2249, perf.

30/2217-27, Skid 10000 gäl/2217-27

TP 2525 li. Estg.

1990