

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO CHEMICALLY TREAT WE	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO OTHERWISE ALTER CAS	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		
	Hobbe, New Mexico	Hay 25, 1951
	Place	Date

OIL CONSERVATION COMMISSION. Santa Fe, New Mexico

Gentlemen:

Following is a notice of intention to	do certain work as described below at	the
ulf dil Corporation	Artesia State	Well No. 3 in W St
Company or Operator	Lease	
of Sec. 19 T. 185	, R	Artesia Field.

.....County. i Alay

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

12 1/2" hole from surface to 214" 9 5/8 " hole from 214" to 484" 7 5/8" OD 29.70# casing set at 484'-cemented with 55 sacks cement 6 3/4" hole from 484" to 1950" 5 1/2 00 14/ casing set at 1949'-commented with 50 sacks comment 5 11/16" hole from 1949' to 2081' 5 11/16" hole plugged back from 2081 to 2060" with 3 sacks cement

JUN 4 1951	Gulf Oil Corporation
Approved, 19	By CD Borland
	Position Asst. Prod. Supit. Send communications regarding well to
DIL CONSERVATION COMMISSION,	Name J. D. Borland
By Coloman	Address Box 1667, Hobbs, New Mexice,
Type OIL AND GAS INSPECTOR	

Plugging Procedure For Artesia State Well No. 3.

- 1. Fill hole full of mud.
- 2. Set Baker Model "K" Cement Retainer in 5 1/2" casing at 1934; plug back below retainer from 2060! to 1934 and above retainer from 1934 to 1926! with cement 37 sacks cement.
- 3. Shoot off 5 1/2" casing at approximately 1465".
- 4. Pull approximately 1465' of 5 1/2 OD casing.
- 5. Place 25' cement plug from 509' to 484'---6 3/4 hole.

6 sacks cement.

6. Place 25' cement plug from 484' to 459'-7 5/8" OD CSG.

7 sacks cement.

- 7. Place bridge 25' down inside 7 5/8" OD casing.
- 8. Fill top 25' of 7 5/8" casing with cement. 7 sacks cement.
- 9. Surface cement plug.
- 10. Place 4" pipe marker inside 7 5/8" casing and extending 4' above mean ground level.

57 sacks cement.

FORMATIONS:

Tansill 205' Yates 500' Artesia Sand 1445' Grayburg Dolomite 1795' , the second second second second

- in the state of the state of
 - A state of the sta
- المراجعة من أسبح محلال إليه المراجع المعنية المعرفي المسجد المراجع المحجور. الأسح المراجع المراجع
- A second sec second sec
 - and the second state of the se
- na serie de la serie de la
- and a second s Second s

يريفهم والعمالي والمراجع المراجع المراجع والمراجع والمراجع والمراجع والمراجع والمراجع والمراجع والمراجع والمراجع

. Sanan karin kakar

,