

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND	FICE
OPE	OR

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

OCT 23 1975

Form C-101
Supersedes C-101
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

<input checked="" type="checkbox"/> OIL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	5. Field or Lease Name Artesia Metex Unit
6. Name of Operator Yates Drilling Company ✓	7. Unit Agreement, if any
8. Address of Operator 207 So. 4th St., Artesia, NM 88210	9. Well No. 24
10. Location of Well UNIT LETTER O, 660 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 18S RANGE 28E NMPM.	11. Field or Lease Name Artesia
12. Elevation (Show whether DF, RT, GP, etc.) NA	13. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

<input type="checkbox"/> PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER	<input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER	SUBSEQUENT REPORT OF: <input checked="" type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER	<input type="checkbox"/> ALTERING OFF LOG <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER
---	--	---	--

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

9/8/75 - Pulled tbg and rods. RIH w/tbg and open hole Lynes packer. Set packer at 1615'. Sand-wtr frac'd with 40,000 gal treated water, 1000 gal 15% NE acid, 25,000# 20-40 sand, 5000# 10-20 sand, 1500# Rock salt and benzoic acid flakes diverting material. Average treating rate 18 BPM at 1800 psig, max 1900 psig. Production rate before - 1 BOPD; after 25 BOPD, 5 BWPD. Well tested 9/24/75.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. L. Loyd TITLE Supt. DATE Oct. 22, 1975
 APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 24 1975
 CONDITIONS OF APPROVAL, IF ANY: