



NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Southwest Production Company, Inc. Booker Bldg, Artesia, New Mexico
State _____ Well No. 1 in _____ of Sec. 20, T. 18 S.
R. 28 E, N. M. P. M. Artesia Field, Eddy County.
Well is 330 feet south of the North line and 1980 feet west of the East line of Section 20
If State land the oil and gas lease is No. E-1821 Assignment No. 1
If patented land the owner is _____ Address _____
If Government land the permittee is _____ Address _____
The Lessee is Southwest Production Co., Inc. Address Artesia, New Mexico
Drilling commenced March 26, 1948 19 _____ Drilling was completed March 18 19 49
Name of drilling contractor S.P. Yates Address _____
Elevation above sea level at top of casing 3603 feet.
The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from 2432 to 2440 No. 4, from _____ to _____
No. 2, from 2501 to 2540 No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from 175 to 180 feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10				263					Water Shut off
8	28			570					Caving Shut Off
7	20	8	J&L	2377	Texas				Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
12	10	263	Set & Pulled			
10	8	570	Set & Pulled			
8	7	2377	75	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters — Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Dowell Acid	3252	9-18-48	2501-40	
		Nitro-Glycerine	90 qt	2-14-49	2923-46	2960
		Nitro-Glycerine	305 qt	2-18-49	2421-2540	2960

Results of shooting or chemical treatment
10 BOPD after acid
3 BOPD after shot

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Surface 3260 PRODUCTION

Put to producing _____ 19 _____
The production of the first 24 hours was December 15 48 and March 20, 1949 after Deepening _____ barrels of fluid of which _____ % was oil; _____ % emulsion; _____ % water; and 27 % sediment. Gravity, Be. 90
If gas well, cu. ft. per 24 hours 10 Gallons gasoline per 1,000 cu. ft. of gas 36 degrees
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Driller _____, Driller
R.O. Jacobs
T.D. Bradshaw, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3rd day of April 1950
Notary Public

My Commission expires _____

Name J.C. Bradshaw, Artesia, New Mexico 4/3/50
Position President
Representing Southwest Production Co., Inc.
Address Artesia, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	35		Sd.
35	60		R.B.
60	150		Sd.
150	175		R.B.
175	180		Water Sand
180	210		Sd, R.B., Caving
210	225		R.B.
225	230		Gyp, R.B.
230	315		Broken
315	330		R.B.
330	380		Anhy
380	390		R.B.
390	445		Mixed
445	478		Anhy
478	495		Gr. Sh & Anhy
495	1022		Anhy
1022	1035		Broken
1035	1570		Anhy & Tr. Sd.
1570	1593		Red Sand
1593	1782		Anhy
1782	1797		Lime
1797	1805		Sd. & Ls.
1805	1875		Anhy
1875	1885		Ls.
1885	1910		Anhy Sandy
1910	1950		Lime
1950	1980		Ls. & Sand, Rainbow S.O.
1980	1995		Lime
1995	2012		Sdy Lime, S.O.
2012	2135		Lime
2135	2155		Sdy Lime
2155	2175		Lime
2175	2180		Sdy Lime
2180	2266		Lime
2266	2280		Gr. Sand, Soft.
2280	2428		Lime
2428	2432		Lime & Sand, S.O.
2432	2437		Sand, S.O.
2437	2501		Lime
2501	2540		Lime, S.O.
2540	2853		Lime
			Original T.D.
			Deepening Record.
2853	2917		Lime
2917	2938		Br. Lime
2938	2995		Lime
2995	3025		Br. Lime
3025	3117		Lime
3117	3143		Br. Lime
3143	3159		Sandy Lime
3159	3175		Br. Lime
3175	3187		Gr. Lime
3187	3220		Lime
3220	3260		Br. Lime
			T.D. 3260