NEW MEXICO OIL CONSERVATION COMMISSION Santa Fc, New Mexico

~~ ¹

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES LOCATE WELL CORRECTLY

•

Southwester	n, Inc.	Hu	Humible State B-11540				
(Corr Well No							
Artesi							
Well is	feet from North	line and	990	feet from	West	line	
of Section							
Drilling CommencedNov							
Name of Drilling Contractor.	Southweater	. Inc.					
Address	Box 1116	Lovingt	on, New	Mexico	••••••		
Elevation above sea level at To Dec. 11		3603	The in	formation given is t	o be kept confide	ential until	

OIL SANDS OR ZONES

No. 1, from	2080	to	2095	No. 4, from	2389 to	23 98
				No. 5, from		
No. 3, from	2382	to	2385	No. 6, from	to	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.							
No. 1, from	to	215	feet.	Rose 50 ft. in hole			
No. 2, from							
No. 3, from							
No. 4, from	to		feet.				

	CASING RECORD								
SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE		
10 2/1	40.00	Used	232	Ter Pet.	232	none	Water shut off		
0 5/0	<u>.</u>	Used	1.95.50	Toy Pat		none	Water shut off		
5 1/2	14	Used	2420 ft.	Float sh	0 0 0-	As shown abo			
/ -/ -						1	1		

	MUDDING AND CEMENTING BECOBD						
SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED	
12	10 2/4	232		Cable tool ri	e 1 -	50 sacha	
10	9 5/9	1.95 50	50	Denton Cement	~ ·	none	
\$ 	5/1/2	2420	100	Denton Cement		100 sacks	
	71 -1 -						

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

10,000 gals. refined oil; 15,6241bs.20-40 sand 2373 to 2398
10,000 gals. refined oil; 10,0001bs.20-40 sand 2080 to 2095
5,000 lbs. 10-20- sand

36 Ball Sealers

Result of Production Stimulation

MENORD OF DRILL-STEM AND SPECIAL TENDS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

				TOOLS	USED				
Rotary tools w	ere used from		feet t	0	feet, a	nd from		feet to	feet
Cable tools we	re used from	0	feet t		feet, a	nd from		feet to	feet
				PRODU	CTION				
				, 19		overi	ng lo	ad oil	
OIL WELL:	The production	during the first	t 24 ho	urs was	•	no ce	rrels of lic	de- quid of which	
								% was s	
	Gravity								
GAS WELL:		· · ·				MCEN	•		, ,
						m.c.r. p	ius		barrels of
	liquid Hydrocart	oon. Shut in Pr	ressure	lbs.				· · · ·	
Length of Tim	ne Shut in								
PLEASE	INDICATE BEI	LOW FORMA	TION	TOPS (IN CON	FORMAN	CE WITI	H GEOGI	RAPHICAL SECTION (OF STATE):
	3/5	Southeastern	New M	fexico				Northwestern New	Mexico
T. Anhy	450		Т.	Devonian			т.	Ojo Alamo	
T. Salt	non	•	T.	Silurian	, 		Т.	Kirtland-Fruitland	
	non			Montoya			Т.	Farmington	
	101			Simpson			T.	Pictured Cliffs	
	149			McKee			Т.	Menefee	••••
-	208			Ellenburger			T .	Point Lookout	<u></u>
T. Grayburg.	218	5	. Т.	Gr. Wash			T.	Mancos	
T. San Andre	s		. Т.	Granite			Т.	Dakota	
T. Glorieta			. Т.	••••••			Т.	Morrison	•••••
T. Drinkard			T.		••••		Т.	Penn	
							Т.	•	
T. Abo			. Т.				Т.		•••••
T. Penn			. T.	••••••			Т.		
T. Miss	·		. T.				Т.	•	••••••
	<u> </u>			FORMATIO	N RECO	RD		· .	
From T	O . Thickness in Feet	F	ormatio	on	From	То	Thickness in Feet	s Formation	n
0 27	5 275	Red be	d						
41 53	0 289	Red be		Anhy					
31 49		Anny &							
496 181		Ante &	: 110	ne & sand					
811 223 233 243		Line A	: s ai	na					

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

	December 29, 1958	
Company or Operator	Address for 1116 Lovington,	a. Mexico
Name I Grallin	Position of Title Perstor	