

WELL LOG

STATE LAND OFFICE

Eddy

COUNTY, NEW MEXICO

Company Snowden & McSweeney Company. Lease No. 647 Assignment No. 123 1/2Well #6 V. H. McNutt. Drilled in SW 1/4 of Sec. 21 Twp. 18S Rng. 28E
(NO. OR NAME)Date Started August 18, 1925. Date Completed September 14, 1925.Depth in Feet 2090'

STANDARD OIL COMPANY, FORT WORTH

FROM	TO	FORMATION
0'	10'	Surface, loose.
10'	20'	Gyp, white, hard.
20'	135'	Sand, red, soft.
135'	150'	Gyp, white, hard.
150'	240'	Bed, red, soft.
240'	280'	Gyp, white, hard.
280'	350'	Bed, red, soft.
350'	370'	Gyp, white, hard.
370'	405'	Bed, red, soft.
405'	415'	Gyp, white, hard.
415'	510'	Salt, white, hard.
510'	525'	Lime, white, soft.
525'	535'	Bed, red, soft.
535'	560'	Gyp, white, hard.
560'	605'	Lime, white, soft.
605'	735'	Gyp, white, hard.
735'	745'	Sand, red, soft.
745'	750'	Bed, red, soft.
750'	800'	Gyp, white, hard.
800'	825'	Lime, white, hard.
825'	830'	Sand, red, soft.
830'	870'	Gyp, white, hard.
870'	875'	Lime, white, hard.
875'	900'	Sand, red, hard.
900'	950'	Gyp, white, hard.
950'	1025'	Sand, red, soft.
1025'	1050'	Lime, pink, hard.
1050'	1080'	Lime, white, hard.
1080'	1125'	Lime, gray, hard.
1125'	1200'	Lime, white, hard.
1200'	1215'	Lime, pink, hard.
1215'	1235'	Lime, white, hard.
1235'	1260'	Lime, white, hard.
1260'	1300'	Gyp, white, hard.
1300'	1350'	Lime, white, hard.
1350'	1375'	Gyp, white, hard.
1375'	1410'	Bed, red, soft.
1410'	1430'	Lime, pink, soft.
1430'	1475'	Lime, white, hard.
1475'	1540'	Lime, pink, hard.
1540'	1560'	Lime, white, hard.
1560'	1605'	Lime, pink, hard.
1605'	1640'	Sand, red, soft.
1640'	1670'	Lime, white, hard.
1670'	1735'	Lime, pink, hard.
1735'	1775'	Lime, white, hard.
1775'	1810'	Lime, pink, hard.
1810'	1845'	Lime, white, hard.
1845'	1859'	Sand, brown. Hole filled up 600' with oil.
1859'	1872'	Sandy lime, hard.
1872'	1920'	Lime, pink, soft.
1920'	1925'	Lime, brown, hard.
1925'	2048'	Lime, white, hard.
2048'	2079'	Sand, brown, soft. Oil sand.
2079'	2090'	Lime, white, hard.

Total depth 2090'

CASING RECORD:

Wood conductor 14'
 10" 285'
 8" 655'
 6 5/8" 1960'

One joint 6 5/8" casing is perforated for 10' to let oil in from 1845' sand. Perforation sets 1838' to 1848'.

Shot by American Glycerin Company 9-16-25 with 140 qts. from 2048' to 2079'.

Shot by American Glycerin Company 9-20-25 with 110 qts. from 1845' to 1860'

Initial production:
 1st 24 hrs. 150 bbls.
 2nd 24 hrs. 180 "

I hereby certify that the above is a true and correct log of well drilled on the above described land.

SNOWDEN & MCSWEENEY COMPANY,

By H. F. Schoover
Supt.



Year	1900	1901	1902	1903	1904	1905	1906	1907	1908	1909	1910	1911	1912	1913	1914	1915	1916	1917	1918	1919	1920	1921	1922	1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999
1900	1901	1902	1903	1904	1905	1906	1907	1908	1909	1910	1911	1912	1913	1914	1915	1916	1917	1918	1919	1920	1921	1922	1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	