

P. O. BOX 2990
SANTA FE, NEW MEXICO 87501Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY

JUN 08 1984

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
647	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>Water Injection</u>		7. Unit Agreement Name
2. Name of Operator <u>American Petrofina Company of Texas</u>		8. Farm or Lease Name <u>McNutt St.</u>
3. Address of Operator <u>P. O. Box 2990, Midland, TX 79702-2990</u>		9. Well No. <u>6</u>
4. Location of Well UNIT LETTER <u>K</u> <u>1618</u> FEET FROM THE <u>south</u> LINE AND <u>2335</u> FEET FROM THE <u>west</u> LINE, SECTION <u>21</u> TOWNSHIP <u>18 S</u> RANGE <u>28 E</u> NMPM.		10. Field and Pool, or Wildcat <u>Artesia</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3563</u>		12. County <u>Eddy</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
 PLUG AND ABANDONMENT ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-16-84 Run cement bond log from 1812 to 1462'. Top cement 1462'.
 5-17-84 Set cement retainer at 1802'. Set 15 sack plug on top of retainer.
 Perforated 4½" casing from 1396-1400'.
 Pumped 135 sk down 4½ casing & got returns on casing & surface pipe.
 5-18-84 Tagged cement at 827'.
 With tubing at 800' pumped 100 sks cement circulated to surface.
 Pulled tbq. Tagged cement at 150'.
 Pumped 20 sks. Circulated to surface.
 Set 4" Pipe marker.

Location has been cleaned & pits filled, ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

J. C. ChapmanTITLE Asst. Dist. Mgr. of Prod DATE 6/7/84

APPROVED BY

ORIGINAL SIGNED
BY LARRY BROOKS
GEOLOGIST - NMOCD

TITLE

DATE

APR 17 1985

CONDITIONS OF APPROVAL, IF ANY:

Post ID-2
4-19-85
P+H