

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
MAY 4 1970

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 647
7. Unit Agreement Name --
8. Farm or Lease Name Lackawanna "A" State
9. Well No. 2
10. Field and Pool, or Wildcat Artesia
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator AMERICAN PETROFINA COMPANY OF TEXAS
3. Address of Operator Box 1311, Big Spring, Texas 79720
4. Location of Well UNIT LETTER J , 1555 FEET FROM THE South LINE AND 2373 FEET FROM THE East LINE, SECTION 21 TOWNSHIP 18S RANGE 28E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3581 Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Start work April 30, 1970

1. Spot 50 sx cement plug on bottom through 2" EUE tubing using mud laden fluid as displacing medium.
2. Pull 6-5/8" casing (1948') Spot 25 sx cement plug at 1500' (Queen Sand)
3. Pull 8-1/4" casing (695') Spot 25 sx cement plug at 304' (Bottom of 10" csg)
4. Place 10 sx cement plug in top of 10" casing and set 4" pipe marker.

JCC/js

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. C. Chapman J. C. Chapman TITLE Production Engineer DATE April 28, 1970

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE MAY 4 1970

CONDITIONS OF APPROVAL, IF ANY: Intervals between plugs filled with mud