OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

ECEIVE

On VIIC

Miscellaneous Reports on Wellson Comm.

Artecia Cilice

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

	ao or repo	rt by checking be	aow.	
EPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON	REPAIRING WELL	
EPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		11	PULLING OR OTHERWISE	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON	DEEPENING WELL	
EPORT ON RESULT OF PLUGGING OF WELL	X			
August 15, 1950		Artesis, New Hexico		
OIL CONSERVATION COMMISSION, ANTA FE, NEW MEXICO. Sentlemen: Sollowing is a report on the work done and the results. Inc Resign Cal Company	ults obtain	ed under the hea	ding noted above at the Malo	o Refiner
Company or Operator		Lease		
SF/4 NE/4 of Sec. 2 Artesia Field Edd	"		, R, N	л. м. Р. м. ,
he dates of this work were as follows:	t 1 to	Angust 9. 19		
				•
otice of intention to do the work was (was see section)			_	19
and appropriate of the property along the same (
na approvai of the proposed plan was (optained	(Cross out incor	rect words.) by phone.	
nd approval of the proposed plan was (*********************** DETAILED ACCOUNT OF Set 10 sax coment plums at 4400***	F WORK	DONE AND RES	SULTS OBTAINED	
	F WORK: 2200*, casing	done and res	Pulled approximately le to surface and ling Co. Supt.	
Set 10 sax cement plugs at 4400°, 1500° of 7° casing and 300° of 8° set regulation dry hole market. Vitnessed by J. O. Miller Name	2200°, casing	and 500°. Filled ho Yates Dr11 Comps	Pulled approximately le to surface and ling Co. Supt.	
Set 10 sax cement plugs at 4400°, 1500° of 7° casing and 300° of 8° set regulation dry hole market. Vitnessed by J. O. Miller	2200°, casing	and 500°. Filled ho Yates Dr11 Comps	Pulled approximately le to surface and ling Co. Supt. or affirm that the information	
Set 10 sax cement plugs at 4400°, 1500° of 7° casing and 300° of 8° set regulation dry hole market. Vitnessed by J. O. Miller Name	easing	and 500°. Filled ho Tates Bril Compa I hereby swear is true and corr Name	Pulled approximately le to surface and ling Co. Supt. or affirm that the information ect. Class. AReas.	
Set 10 sax cement plugs at 4400°, 1500° of 7° casing and 300° of 8° set regulation dry hole market. Vitnessed by J. O. Miller Name Subscribed and sworn before me this 15th	easing	and 500°. Filled ho Tates Pril Comps I hereby swear is true and corr	Pulled approximately le to surface and ling Co. Supt. or affirm that the information ect. Class. AReas.	
Set 10 sax cement plugs at 4400°, 1500° of 7° casing and 300° of 8° set regulation dry hole market. Vitnessed by J. O. Miller Name Subscribed and sworn before me this 15th	S. P	Tates Drilled ho Filled ho Fates Drilled ho I hereby swear is true and corr Name Position	Pulled approximately le to surface and ling Co. Supt. or affirm that the information ect. Class. AReas.	given above

Remarks:

AUG 30 1050

Title