

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New MexicoWELL RECORD
OLD WELL DEEPEMED

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

S. P. Yates

311 Carper Building, Artesia, New Mexico

Company or Operator

State G

Well No.

1

in NW/4 SW/4

Address

23

T. 18S

Lease

R. 28E, N. M. P. M., Artesia, Field, Eddy, County.

Well is 3710 feet south of the North line and 5030 feet west of the East line of Section 23

If State land the oil and gas lease is No. E-1392 Assignment No.

If patented land the owner is, Address.

If Government land the permittee is, Address.

The Lessee is, Address.

Drilling commenced 1/19/50 19. Drilling was completed 3/6 1950

Name of drilling contractor S. P. Yates, Address Artesia, New Mexico

Elevation above sea level at top of casing 3545 feet.

The information given is to be kept confidential until 19.

OIL SANDS OR ZONES

No. 1, from 2529' to 2545' No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
5 1/2	14#	8	NAT	2514'	60 Gauge Guide				Production String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Nitro	120 qts	3/30/50	2550 to 2545	2555' 2870'

Results of shooting or chemical treatment: Treated with 6000 gallons of acid below 2800' -

Negative results

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to T.D. feet, and from feet to feet

PRODUCTION

Put to producing 3/6/ 1950

The production of the first 24 hours was 50 barrels of fluid of which 100% was oil; %

emulsion; % water; and % sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

W. F. Keith, Driller

Frank Sloan, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 10th

day of March, 1950

Delma S. Matthews

Notary Public

Artesia, New Mexico 3/10/50

Name Hugh W. Barry

Position Office Manager

Representing S. P. Yates

