

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-015-02023

Indicate Type of Lease

STATE ☒

FEE ☐

State Oil & Gas Lease No.

E-1287

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

Name of Operator

SDX Resources, Inc.

Well No.

1

Address of Operator

PO Box 5061, Midland TX 79704

Pool name or Wildcat

Artesia QN-GB-SA

Well Location

Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The West Line

23 Section 18S Township 28E Range NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)

3507' GR

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Present Condition:

TD: 2770'

8-5/8", 24# csg @ 452'. Cmt'd w/52 sx.

5" csg @ 2747'. Cmt'd w/150 sx. TOC 1800'.

Perfs 2517' - 37'. Fraced w/20,000 gal. Permanent BP @ 2490' w/10' cmt on top.

Perfs 2455' - 2462'. Fraced w/10,000 gal. CIBP @ 2310' w/35' cmt on top.

Perfs 2207' - 24'. Fraced w/20,000 gal.

Proposed P&A Procedure:

TIH to 2100' & circ hole w/mud laden fluid & spot 25 sx plug 2100' - 1790'. TAG

Cut & pull 5" csg from 1790'. 25sx cement Plug 50' & 50' out 5" csg plug. TAG

TIH & spot 25 sx plug 1100' - 1000'. TAG. BX salt plug.

Spot 25 sx plug 500' - 400'. TAG

Set 10 sx surface plug.

X Perf. 8 5/8" @ 50'. Circ. cement to surface inside & outside 8 5/8" csg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Bonnie Atwater

TITLE Regulatory Tech.

DATE 11-05-97

TYPE OR PRINT NAME Bonnie Atwater

TELEPHONE NO. 915/685-1761

(This space for State Use)

APPROVED BY

mae stuffer

TITLE Field Rep. II

DATE 4-9-99

CONDITIONS OF APPROVAL, IF ANY:

* Brine gel between all cement plugs.

* Notify NMOCN to witness Plugging Operations.

30-015-02023

K-23-18-28

SDX Res. Inc. Mesa FAF ST. #1

Tops
T. SALT 390'
B. SALT 610'

8 5/8"
452'
w/525X.

= Perf 2207'-24'
= Perf 2455'-2462'
= Perfs 2517'-32'

5"
2747' }

w/1505X
TCC-1800'
TD-2770'

- * Perf 8 5/8" csg 250'. Circ. cement to surface inside & outside 8 5/8" csg.
- * 255X 500'-400'. TAG
- * 255X cement Plug 1100'-1000'. TAG.
- * 255X cement Plug 50' in. & 50' out of 5" csg stub. TAG
- * Cut & Pull 5" csg @ 1790'.
- * 255X 2100'-1790'. TAG
- * CTBP @ 2310' w/35' cmt.
- * CTBP @ 2490' w/110 SX

Mesa FAF #1

P+A Proposal

