

County Eddy Depth 2700' Pool Artesia*

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company Resler & Yates, et al Well No. 129 Lease State

1980 Feet from N. Line 990 Feet from E. Line, Sec. 23 Twp. 18S Rge. 28E

<i>Spl.</i>	Land <u>State</u>	Contractor <u>S. P. Yates Drlg. Co.</u>	<u>CT</u>
T. A	Elevation <u>3506</u>	Spudded <u>4-6-56</u>	Completed <u>6-22-56</u>
T. X <u>425</u>	T. Tu	Total Depth <u>2873</u> li	P. B.
B. X <u>615</u>	T. Full	Top Pay <u>2800</u>	District <u>7</u>
T. Del Li	T. DR	I.P.F. <u>80</u>	BOPD
T. Del Sd	T. Wich A.	Base on	BO <u>24</u> Hrs.
T. Y	T. Abo	Choke: <u>Open</u>	Inch
T. SR	T. WC	Tubing <u>2</u> @ <u>2850</u>	Ft.
T. Q <u>1760</u>	T. Hu	Press:	Tbg. Csg.
T. PR	T. Per-Pe	GOR	Gravity <u>36</u>
T. GB	T. Penn	Effective Perfs.:	
T. SA <u>2548</u>	T. Strawn	<u>120 h 2800-30</u>	
T. Glo	T. Miss		
T. Blby	T. WF		
T. CF	T. Dev	Acid, Frac & Shooting Record:	

CSG. & CEMENTING RECORD

Size	Feet	Sax Cement
<u>8 1/2</u>	<u>446</u>	<u>100</u> ✓
<u>5 1/2</u>	<u>2840</u>	<u>250</u> ✓

T. Sil	<u>10,000</u> R/A	From <u>2800</u>	To <u>2830</u>
T. Fuss	<u>10,000</u> R/A	From <u>OH 2840</u>	To <u>2873</u>
T. Mon		From	To
T. Simp		From	To
T. McK			
T. Ell			
T. G.W.			
T. Gr		SHOWS	
T.	<u>SS/91237-40</u>		
T.	<u>S/O 2537-48</u>	Fail 10' in C 1 hr.	
T.	<u>S/O 2689-2700</u>		
T.	<u>S/</u>		
T.	<u>S/</u>		
T.	<u>S/</u>		

4-11-56	Drlg. 440' salt, Water @ 405', 100'	<u>4 2873 li</u>
	in hole	<u>TD 2873 li, w/o 4 1/2 cu</u>
	<u>4 840 anky</u>	<u>TD ✓</u>
	<u>4 1320 anky + li.</u>	<u>June 20 TD 2873 li, w/o</u>
	<u>4 1875 li + sh</u>	<u>Before Comp.</u>
	<u>4 2225 li</u>	<u>TD 2873 li,</u>
	<u>4 2493 ✓</u>	<u>perf 120 h 2800-30</u>
	<u>4 2628 li</u>	<u>ran 2" w/ pkr @</u>
		<u>2835' to thru</u>

tblg pte OH 2840-73 w/10,000 R/A
& then cap above plus the page
2800-20 w/10,000 R/A