

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

NOV 12 1992

O. C. D.

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☐

6. State Oil & Gas Lease No.

B-11276-2

7. Lease Name or Unit Agreement Name

Cowtown Unit Tract 4

8. Well No.

402

9. Pool name or Wildcat

Artesia On Gb SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Anadarko Petroleum Corporation

3. Address of Operator

P. O. Drawer 130, Artesia, N. M. 88211-0130

4. Well Location

Unit Letter E : 1320 Feet From The North Line and 330 Feet From The West Line

Section

24

Township

18S

Range

28E

NMTM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3513 GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. RUPU. GIH with CIBP on tbg. Set at ²⁵⁵⁰~~2650~~ to shut off SA perfs.
Circulate hole with salt gel mud.

2. Spot 35' cement on top of CIBP. This plug covers SA formation.

3. Spot 25 sx Class C with 3% CaCl from 2300' up to 2065'. This plug covers Grayburg formation top. TOH.

4. Tag top of plug with perf gun. Pull up and perf 4 squeeze holes at 730' (100' below salt). GIH with pker and cement squeeze with 25 sx Class C with 3% CaCl, leaving 100' cement in and out of casing. This plug covers base of salt.

Cont. on next page.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mike Braswell

TITLE

Field Foreman

DATE

11-12-92

TYPE OR PRINT NAME

Mike Braswell

TELEPHONE NO. 677-2411

(This space for State Use)

APPROVED BY

[Signature]

TITLE

[Signature]

DATE

11/13/92

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico, Energy, Minerals and Natural Resources Department

[Signature]



12. Describe Proposed or Completed Operations. Page 2.

5. Tag top of plug with perf gun. Pull up and perf 4 squeeze holes at 274' (50' above top of salt). GIH with pker and cement squeeze with 25 sx Class C with 3% CaCl, leaving 100' cement in and out of casing. This plug covers top of salt.
6. Tag top of plug and spot 50' surface plug.
7. Cut off all casing and anchors below surface: Set P&A marker: Clean and level location.

Cowtown Unit Tract 4, No. 402

Unit Letter E

1320' FNL & 330' FWL

Sec 24, T18S, R28E

Eddy Co., New Mexico

Elev 3513'

10" Hole
8 5/8" @ 324' w/ 25 SXS

← Top of salt @ 324'

← Base of salt at 630'

← Top of GB @ 2228'
7" Hole

5 1/2" @ 2880' w/ 90 SXS

← Top of SA @ 2582'

perfs

2560-2570

2696-2698

2700-2702

2708-2714

Open Hole

2880-2903

TD 2903

QKSE
4-10-91