	NEW MEXICO ERALS DEPARTMENT		
LITERIOT AND IT		NSERVATION DIVISION	
DISTRIB		P. O. BOX 2084 RECEIVED	Form C-103 Revised 19-1-78
BANTA FE	SANT	A FE, NEW MEXICO 87501	Ketised 19-1-70
FILE			Su, Indicate Type of Louise
U.S.G.S.		MAR 2 5 1983	State X Fee
LAND OFFI	E		5. State Oll 6 Gas Leuse No.
OPERATOR		O. C. D.	647
		EPORTS ON WELLS	
(DO NOT U	SUNDRY NUTICES AND R THIS FORM FOR PROPOSALS TO DAILL OR TO U USE "APPLICATION FOR PERMIT -" (FORM	EPUN IS UN WELLS EEPEN ON PLUG BACK TO A DIFFERENT RESERVOIR, I C.1011 FOR SUCH PROPOSALS.)	7. Unit Agreement Name
011.		n Injector	8. Farm or Lease Name
2. Name of Operator DEPCO, INC.			State 647 AC 711
J. Address of Operator			9. Well No.
800 Central, Odessa, Texas 79761			82
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER _	F 2310 FERT FROM TH	North Line and 2310 FEET FRI	Artesia O GBR, SA.
West	27	NSHIP 185 RANGE 28e NMP	
THE WEST	LINE, SECTIONTOWN	N3HIP RANGE HMP	<u></u>
TITITITE.	MININI IS. Elevation	(Show whether DF, RT, GR, etc.)	12. County
		3585 GR.	Eddy
ib. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
			
PERFORM REMEDIA	WORK PLUG AN	D ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABAS	ном	COMMENCE CRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CA	ING CHANGE	PLANS CASING TEST AND CEMENT JQB	
		OTHER	
OTHER			
17. Describe Prop	med or Completed Operations (Clearly state of	all pertinent details, and give pertinent dates, includi	ing estimated date of starting any proposed
work) SEE RU	LE 1103.		•
1-18-83 Ran packer and established a rate of 2 BPM @ 1250 psi. Pulled packer and ran a cement retainer and set at 2178'. Pumped 200 sx. cement leaving 40'			
	cement plug.		
1-19-83	1-19-83 Tagged plug at 1622' with wireline. Shot 3 squeeze holes at 675'. Ran		
	tubing with packer and set	at 561' pumped 100 sx. cement.	
1-20-83 Tagged plug at 660' with wireline. Could not unset packer. Shot tubing off			
1-20-83		ireline. Could not unset packer	· Shot tubing off
	at 556'.		
1 01 00	Rumped 120 ex compart foll	owed by six sx sand and 150 sx.	cement that filled
1-21-83 Pumped 120 sx. cement followed by six sx. sand and 150 sx. cement that filled the well bore back to the surface. Set dry hole marker.			
	the well bore back to the	Surface. Det dry nore marker.	
	Plugging witness by Mr. St	ubbfield & Mr. Williams with the	NMOCC. 2
	x F 3		
			Past FD 3
			HAT
18. I hereby certif	that the information prove is true and comp	lete to the best of my knowledge and belief.	
	0///		2 24 22
Lean	Leon Standard	Field Engineer	
	L P.I.	cst. 1 · I	7/72/00
APPROVED	Many Meets	TITLE Kitologest	DATE / C.2/ 5-2
CONDITIONS OF	APPROVAL, IF ANYI	Ĵ.	· 1