

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA OF ACRES
LOCATE WELL CORRECTLY

Resler Oil Co.

Artesia, New Mexico

Malco-Resler-Yates State 87 in NW/4 NE/4 of Sec. 27 T. 18 S
R. 28 E N. M. P. M. Artesia Field, Eddy County.
Well is 330 feet south of the North line and 2310 feet west of the East line of Sec. 27
If State land the oil and gas lease is No. 647 Assignment No.
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Malco-Resler-Yates Address Artesia, New Mexico
Drilling commenced 11-13-1947 19 Drilling was completed 1-2-1948
Name of drilling contractor S. P. Yates Address Artesia, New Mexico
Elevation above sea level at top of casing 3592 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 2770 to 2833 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8"	28 1/2	8	S.H	591'	Texas				Salt String
7"	20 7/8	8	J&L	2577'	Guide				Prod. String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8 5/8"	591'	50	Halliburton		
8"	7"	2577'	100	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		20% acid	1000 Gal	12-21-47	2530' to 2625'	2625'
		20% acid	2000 Gal	1-1-48	2783' to T.D.	2833'

Results of shooting or chemical treatment Production increased from estimated
24 B P D to 200 B P D.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 2833 feet, and from feet to feet

PRODUCTION

Put to producing 1-1-1948
The production of the first 24 hours was 200 barrels of fluid of which 100 % was oil;
emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

C. V. Miller Driller
D. A. Miller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 2nd

Artesia, New Mexico 1-2-48

day of January 1948

Name Hugh W. Garry

Notary Public

Position Office Manager

My Commission expires

Representing Resler Oil Co.
Company or Operator
Address Artesia, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0'	90	90	Sand & top soil
90'	300'	210	Sand & Red Rock
300'	400'	100	Red Rock
400'	485'	85	Red bed
485'	545'	60	Salt
545'	1785'	1240	Anhydrite
1785'	1805'	20	Red sand
1805'	2055'	250	Anhydrite
2055'	2833'	778	Lime
2833'	T. D.		