

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
NM 647	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator International - Yates		8. Farm or Lease Name State 647
3. Address of Operator P. O. Box 427, Artesia, New Mexico		9. Well No. 87
4. Location of Well UNIT LETTER <u>B</u> , <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>27</u> TOWNSHIP <u>18 S.</u> RANGE <u>28 E.</u> N.M.P.M.		10. Field and Pool, or Wildcat Artesia
15. Elevation (Show whether DF, RT, GR, etc.) 3596' GL		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 280' 4½" OD, 9.5#, J-55 liner, top of liner @ 2557'. Pumped in 140 bbls. salt water, 500 gallons MCA acid in two stages and 50 bbls. fresh water. Cemented with 50 sks. Incor Pozmix with 2% gel, 1% CFR-2 and 8# NACL/ sk. Set liner hanger broke off safety joint circulated out 15 sks. cement. Ran G/R Neutron Log and perforated San Andres 2782' to 2827', perforated Loco Hills Zone 2236' to 2257'. Sand-oil treated each zone with 20000# sand using straddle packers.

Pulled packers and put well on pump.

RECEIVED

JUL 22 1965

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald E. Brown TITLE District Engineer DATE 7-21-65

APPROVED BY W. L. Timm TITLE Oil and Gas Inspector DATE JUL 22 1965

CONDITIONS OF APPROVAL, IF ANY: