

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). Submit in triplicate. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Attach map showing location of well on section.

National Supply Company (Formerly Quillen & Bonnett) Box 491, Artesia, N.M.

Compton-State Well No. 1 in SE 1/4 of Sec. 27 T. 18S

R. 28 N. 1/4 P. M. Artesia Field, Eddy County.

Well is 1070 feet North of the South line and 1070 feet west of the East line of Section

If State land the oil and gas lease is No. 647 Assignment No. 234

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced September 7, 1925 Drilling was completed December 10, 1925

Name of drilling contractor McGolin Address Unknown

Elevation above sea level at top of casing 3572 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 1280 to 1282 No. 4, from to

No. 2, from 2228 to 2231 No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 300 to 320 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	FORWARDS PER FOOT	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
10	32			318				Water Shut Off
7"	17			793				Casing

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	10"	318	Set			
	7"	755	Set			

PLUGS AND ADAPTERS

Heaving plug Material Length Depth Set

Adapters Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 2505 feet, and from feet to feet

PRODUCTION

Put to producing Dry 19

The production of the first 24 hours was barrels of fluid of which % was oil: %

emulsion; % water; and % sediment. Gravity, Ba.

If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Unknown Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 12th

day of 1925

Notary Public

My Commission expires

12th 1925

Name W. T. Shannon W. T. Shannon

Position Agent

Representing National Supply Company

Company or Operator

Address Box 491, Artesia, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	7	7	Caliche
7	95	88	Gypsum White
95	120	25	Red Beds
120	300	180	Red Rock
300	314	14	Red Sand (Water 300-320)
314	430	116	Gypsum
430	440	10	Red Rock & Shale
440	460	20	Red Gypsum
460	472	12	Red Shale
472	485	13	Gypsum
485	490	5	Shale
490	495	5	Gypsum, Hard
495	570	75	Shale
572	620	48	Salt
620	690	70	Red Salt
690	715	25	White Lime
715	735	20	Red Shale
735	825	90	Hard White Lime
825	895	70	Grey Shale
895	930	35	White Gypsum
930	935	5	Soft Blue Shale
935	985	50	White Gypsum
985	1000	15	Pink Gypsum
1000	1005	5	Red Shale
1005	1065	60	Pink Gypsum
1065	1197	132	Soft Red Shale
1197	1295	98	Hard Lime (S/S 1230-82)
1295	1335	40	White Lime
1335	1700	365	White Lime & Shale
1700	1806	106	Pink Lime
1806	1848	42	Pink Gypsum
1848	1880	32	Red Sand
1880	1950	70	Lime & Shale
1950	1980	30	White Lime
1980	2025	45	Sand Red
2025	2070	45	Shale, Red
2070	2106	36	Hard Red Sand
2106	2160	54	Sandy Red Shale
2160	2175	15	White Lime
2175	2228	53	Hard White Lime
2228	2231	3	Sandy Lime (Show Oil)
2231	2250	19	Hard Lime
2250	2303	53	Grey Lime
2303	2330	27	Sand
2330	2503	173	Hard Grey Lime

TD 2503