

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION **RECEIVED**

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

FEB 15 '90

O. C. D.

WELL API NO.

30-015-02121

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

647

7. Lease Name or Unit Agreement Name

Resler Yates State

8. Well No.

48

9. Pool name or Wildcat

Artesia - ON GB SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER

Plugged &
Abandoned

2. Name of Operator

Arch Petroleum Inc.

3. Address of Operator

Suite II-A, 777 Taylor St. Ft. Worth, Tx 76102

4. Well Location

Unit Letter P : 246 Feet From The South Line and 878 Feet From The East Line

Section 29

Township 18S

Range 28E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3540'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

01/31/90 - Removed 22" Diameter x 18" long cement plug in top of hole. Went in the hole with 7 3/4 bit to 35' and drilled 6' cement to top of 10 3/4 casing. Drilled 5' of cement inside 10 3/4 to 46'. Drilled on wood plug in 10 3/4 casing at 267'. Trip out of hole. SDON.

02/01/90 - Ran in hole to 267', drilled and pushed wood plug to top of old shot hole at 2003'. Plug fell to side. Drilled cement plug from 2020' to 2046'. Drilled to 2047'. Trip out of hole. SDON.

02/02/90 - Trip in hole and pump 200 barrels Halliburton Gel. 10 3/4 casing fell to the side supported only by 2 3/8 tubing string. Decided to P & A. Pulled tubing to 1595' and set 50 SX Class "C" with #25 Floseal and 4% CACL. Trip out of hole. SDON.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jim B. Paschall

TITLE V. P. OPERATIONS

DATE 2/12/90

TYPE OR PRINT NAME Jim B. Paschall

TELEPHONE NO. 8173329209

(This space for State Use)

APPROVED BY _____ TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Post ID-2
3-2-90
P4A