	RECEIVED			یر اور در در ایس در در این ایر اور ای ای ای در دارسا است		مرتبي الم
DISTRIBL	UTION	4		ليسر بعده لا يع مدر مسر	r	Form C-103 Supersedes Old
SANTA FE		NEV	MEXICO OIL CON	SERVATION COMMISS		C-102 and C-103
U.S.G.S.		-		142-24 - 27 - 27 - 4 142-24 - 24 - 27 - 4 143-24 - 24 - 24 - 24 - 24 - 24 - 24 - 24		Effective 1-1-65
LAND OFFIC	Ē	-				5a. Indicate Type of Lease
OPERATOR		-[and the second s		State XX Fee
		1	ŕ	uk (Luluy, Deradz		5. State Oil & Gas Lease No
100	SUNDA		ND PERCOTS O			647
100 NOF	USE THIS FORM FOR PRO	TON FOR PERMIT	OR TO DEEPEL OR PLUG	N WELLS BACK TO A DIFFERENT RESENDED	RVOIR.	
WELL XX	GAS					7. Unit Agreement Name
Name of Opera	WELL	OTHER-				and a second realized
AMERICAN	PETROFINA COM		1			8. Farm or Lease Name
						Resler Yates State
Box 1311,	Big Spring,	Texas 797	20			S. Well No.
i zooation 51 ne	SE/NE	footage no	t available			10. Field and Pool, or Wildoat
UNIT LETTER	<u> H </u>	00 / FEET FI	ROM THE DOUT	- LINE AND 5707		
THE ECIN	+ 7				FEET FROM	Artesia
····· <u>·····</u>	LINE, SECTIO	N29	_ TOWNSHIP] {	S FANGE	<u>28Е _ умрм.</u>	AHHHHHHHHH
MMM	<u> </u>	15. Ele	wation (Show whether			
1111111	11111111111		:	569 0-		12. County
	Check A	ppropriate Bo	ox To Indicate N	lature of Notice, Re		Eddy Allilli
	NOTICE OF IN	TENTION TO:			port of Oth	er Data
ERFORM REMEDIA					DUCQUENT	REPORT OF:
EMPORARILY ABAN		PL	UG AND ABANDON	REMED.AL WORK		ALTERING CASING
ULL OR ALTER CA	<u></u>			COMMENCE DRILLING OPNS		PLUG AND ABANDONMENT TY
		CH	ANGE PLANS	CASING TEST AND CEMENT	LCA	تحتصفه
					·	
OTHER				отнек		[
	osed or Completed Ope	rations (Clearly s	tote all partinent day		····	
	osed or Completed Ope L E 1103.	rations (Clearly s	tate all pertinent deta		····	stimated date of starting any proposed
. Describe Prope work) SEE RU				ils, and give pertinent dat	es, including e	
. Describe Prope work) SEE RU	Ran 2-3/8" t	ubing to 20	20° and spot	ils, and give pertinent dat	es, including e	
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin	ubing to 20 placing med	20° and spot	tils, and give pertiment dat ted 50 sx cement	es, including e	om using mud laden
. Describe Prope work) SEE RU	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t	ubing to 2(placing med g up to 150 ubing with	020° and spot lium. 00° and spott	tils, and give pertiment dat ted 50 sx cement ed 25 sx cement.	es, including e	om using mud laden
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" to Pumped in 50	ubing to 2(placing med g up to 150 ubing with sx cement	20 [°] and spot ium. 00 [°] and spott 8-5/8" tensi.	ted 50 sx cement. ed 25 sx cement. on packer and se	es, including e	om using mud laden
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50	20 [°] and spot lium. 0 [°] and spott 8-5/8 [°] tension plug and shut	ted 50 sx cement ed 25 sx cement. on packer and se well in. Unsea	es, including e on botto t in bott ted packe	om using mud laden
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still b	20 [°] and spot ium. 0 [°] and spott 8-5/8 [°] tensi. plug and shut sx. Shut we	ted 50 sx cement ed 25 sx cement. On packer and se well in. Unsea	es, including e on botto t in bott ted packe	om using mud laden om of 8-5/8" casing or and reset.
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in ad Opened well a Ran 800° of 2 displacing me	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul	20 [°] and spot ium. 00 [°] and spott 8-5/8" tension plug and shut of sx. Shut we ad small back ng, spotted 2	ted 50 sx cement ed 25 sx cement. on packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plug	es, including e on botto t in bott ted packe packer. g using m	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 5C Pumped in add Opened well a Ran 800° of 2 displacing me Reran 680° of	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul E 2-3/8" tu	20 [°] and spot ium. 0 [°] and spott 8-5/8 [°] tension plug and shur sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot	ted 50 sx cement ed 25 sx cement. on packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plug	es, including e on botto t in bott ted packe packer. g using m	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a Ran 800 [°] of 2 displacing me Reran 680 [°] of Shut in 24 hr	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul 5 2-3/8" tu	20 [°] and spot ium. 00 [°] and spott 8-5/8 [°] tension plug and shur o sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ob	ted 50 sx cement and give pertiment dat ed 25 sx cement. on packer and se well in. Unsea all in. t flow. Pulled p 5 sx cement plug ted additional 2	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a Ran 800 [°] of 2 displacing me Reran 680 [°] of Shut in 24 hr	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul 5 2-3/8" tu	20 [°] and spot ium. 00 [°] and spott 8-5/8 [°] tension plug and shur o sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ob	ted 50 sx cement and give pertiment dat ed 25 sx cement. on packer and se well in. Unsea all in. t flow. Pulled p 5 sx cement plug ted additional 2	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a Ran 800 [°] of 2 displacing me Reran 680 [°] of Shut in 24 hr	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul 5 2-3/8" tu	20 [°] and spot ium. 00 [°] and spott 8-5/8 [°] tension plug and shur o sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ob	ted 50 sx cement and give pertiment dat ed 25 sx cement. on packer and se well in. Unsea all in. t flow. Pulled p 5 sx cement plug ted additional 2	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as
. Describe Propo work) see Ru 11-29-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a Ran 800 [°] of 2 displacing me Reran 680 [°] of Shut in 24 hr	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul 5 2-3/8" tu	20 [°] and spot ium. 00 [°] and spott 8-5/8 [°] tension plug and shur o sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ob	ted 50 sx cement and give pertiment dat ed 25 sx cement. on packer and se well in. Unsea all in. t flow. Pulled p 5 sx cement plug ted additional 2	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
. Describe Propo work) SEE RU 11-29-69 12-2-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a Ran 800 [°] of 2 displacing me Reran 680 [°] of Shut in 24 hr	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul 5 2-3/8" tu	20 [°] and spot ium. 00 [°] and spott 8-5/8 [°] tension plug and shur o sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ob	ted 50 sx cement and give pertiment dat ed 25 sx cement. on packer and se well in. Unsea all in. t flow. Pulled p 5 sx cement plug ted additional 2	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
Describe Prop work) SEE RU 11-29-69 12-2-69	Ran 2-3/8" t fluid as dis Pulled tubin Ran 2-3/8" t Pumped in 50 Pumped in add Opened well a Ran 800 [°] of 2 displacing me Reran 680 [°] of Shut in 24 hr	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul 5 2-3/8" tu	20 [°] and spot ium. 00 [°] and spott 8-5/8 [°] tension plug and shur o sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ob	ted 50 sx cement and give pertiment dat ed 25 sx cement. on packer and se well in. Unsea all in. t flow. Pulled p 5 sx cement plug ted additional 2	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
Describe Prope work) SEE RU 11-29-69 12-2-69 12-2-69 CC/js /2/70	Ran 2-3/8" to fluid as dis Pulled tubin Ran 2-3/8" to Pumped in 5C Pumped in add Opened well a Ran 800° of 2 displacing me Reran 680° of Shut in 24 hr Placed 10 sx	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul E 2-3/8" tu cement plu	020 [°] and spot ium. 00 [°] and spott 8-5/8 ¹¹ tension plug and shur 0 sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ok. g in top of 8	ted 50 sx cement ed 25 sx cement. on packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plup ted additional 2 -5/8" casing and	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
Describe Prope work) SEE RU 11-29-69 12-2-69 12-2-69 CC/js /2/70	Ran 2-3/8" to fluid as dis Pulled tubin Ran 2-3/8" to Pumped in 5C Pumped in add Opened well a Ran 800° of 2 displacing me Reran 680° of Shut in 24 hr Placed 10 sx	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul E 2-3/8" tu cement plu	020 [°] and spot ium. 00 [°] and spott 8-5/8 ¹¹ tension plug and shur 0 sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ok. g in top of 8	ted 50 sx cement ed 25 sx cement. on packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plup ted additional 2 -5/8" casing and	es, including e on botto t in bott ted packet packer. g using m 25 sx cem	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.
Describe Prope work) SEE RU 11-29-69 12-2-69 12-2-69 CC/js /2/70	Ran 2-3/8" to fluid as disp Pulled tubing Ran 2-3/8" to Pumped in 50 Pumped in add Opened well a Ran 800° of 2 displacing me Reran 680° of Shut in 24 hr Placed 10 sx	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul E 2-3/8" tu cement plu	20 [°] and spot ium. 00 [°] and spott 8-5/8" tensid plug and shut or sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ok. g in top of 8	ted 50 sx cement ed 25 sx cement. On packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plup ted additional 2 5-5/8" casing and	es, including e on botto t in bott ted packer gacker. g using m 25 sx cem d set 4-1	om using mud laden om of 8-5/8" casing er and reset. Aud laden fluid as ment plug. /2" pipe marker.
Describe Prope work) SEE RU 11-29-69 12-2-69 12-2-69 CC/js /2/70	Ran 2-3/8" to fluid as disp Pulled tubing Ran 2-3/8" to Pumped in 50 Pumped in add Opened well a Ran 800° of 2 displacing me Reran 680° of Shut in 24 hr Placed 10 sx	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul E 2-3/8" tu cement plu	20 [°] and spot ium. 00 [°] and spott 8-5/8" tensid plug and shut or sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ok. g in top of 8	ted 50 sx cement ed 25 sx cement. On packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plup ted additional 2 5-5/8" casing and	es, including e on botto t in bott ted packer gacker. g using m 25 sx cem d set 4-1	om using mud laden om of 8-5/8" casing er and reset. Aud laden fluid as ment plug. /2" pipe marker.
Describe Prope work) SEE RU 11-29-69 12-2-69 12-2-69 CC/js /2/70	Ran 2-3/8" to fluid as disp Pulled tubing Ran 2-3/8" to Pumped in 50 Pumped in add Opened well a Ran 800° of 2 displacing me Reran 680° of Shut in 24 hr Placed 10 sx	ubing to 20 placing med g up to 150 ubing with sx cement ditional 50 and still h 2-3/8" tubi edium. Pul E 2-3/8" tu cement plu	20 [°] and spot ium. 00 [°] and spott 8-5/8" tensid plug and shut or sx. Shut we ad small back ng, spotted 2 led tubing. bing and spot eld ok. g in top of 8	ted 50 sx cement ed 25 sx cement. On packer and se well in. Unsea ell in. c flow. Pulled p 5 sx cement plup ted additional 2 5-5/8" casing and	es, including e on botto t in bott ted packer gacker. g using m 25 sx cem d set 4-1	om using mud laden com of 8-5/8" casing er and reset. nud laden fluid as ent plug.