

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

WELL RECORD

DEEPENING RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Malco-Hesler-Yates Company or Operator
Artesia, New Mexico Address
State Well No. 28 In NE NE of Sec. 32 T 18 S
N 22 E N. M. P. M. Artesia Field, Eddy County.
Well is 880 feet south of the North line and 220 feet west of the East line of Sec. 32
If State land the oil and gas lease is No. 647 Assignment No.
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced Feb. 10, 1947 Drilling was completed March 22, 1948
Name of drilling contractor Flynn, Nelson and Yates Address Artesia, New Mexico
Elevation above sea level at top of casing 3538 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 3150 to 3126 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
	NONE								

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		NONE				

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 2050 feet to 3126 feet, and from feet to feet
Cable tools were used from 2050 feet to 3126 feet, and from feet to feet

PRODUCTION

Put to producing Dry hole Was plugged and abandoned
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

L.P. Davis Driller
Paris Davis Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 3rd day of May 1948
Notary Public
My Commission expires
Artesia, N.M. 5-2-48
Name Secretary Operating Committee
Position
Representing Malco-Hesler-Yates Company or Operator
Address Carper Bldg. Artesia. N.M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
2039	2135		buff dolomite
2135	2280		Sandy dolomite
2280	2420		buff dolomite
2420-	2480		grey sandy dolomite
2480	3126		buff dolomite

Top San Andres 2280'

T. D. 3126