

Santa Fe, New Mexico

WELL RECORD RECEIVED
NOV 15 1964

Mail to District Office, Oil Conservation Commission, to which Form C-1 has been sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Fund submit 6 Copies

**AREA 640 ACRES
LOCATE WELL CORRECTLY**

McCoy and Stevens

Ohio-State

(Company of Operator)

(L-250)

Well No. 1, in SW $\frac{1}{4}$ of NW $\frac{1}{4}$, of Sec. 36, T. 18S, R. 28E, NMPM.

Undesignated Pool, Eddy County.

Well is 1980 feet from North line and 660 feet from West line

of Section 36 If State Land the Oil and Gas Lease No. is 182

Drilling Commenced July 15, 19 61 Drilling was Completed September 3, 19 61

Name of Drilling Contractor.....**Kincaid and Watson Drilling Co.**.....

Address P. O. Box 498, Artesia, New Mexico

Elevation above sea level at Top of Tubing Head.....**3427**..... The information given is to be kept confidential until

OIL SANDS OR ZONES

No. 1, from 1290 to 1295 RBSO No. 4, from _____ to _____

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 170 to 175 feet.

No. 2, from 2886 to 2898 feet. 1/2 blr. per hr.

No. 3, from 2930 to 2945 feet. 1 bailer per hour

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	Used	360	Hal			Water String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
18"	8 5/8	360	50	Denton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.

..Depth Cleaned Out.

OIL CONSERVATION COMMISSION	
ARTESIA DISTRICT OFFICE	
No. Copies Received	
DISTRIBUTION	
NO.	FURNISHED
OPERATOR	
SANTA FE	
PROBATION OFFICE	
STATE LAND OFFICE	
U. S. G. S.	
TRANSPORTER	
FILE	
BUREAU OF MINES	

[illegible]

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing....., 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....					
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....					
B. Salt.....	T. Montoya.....	T. Farmington.....					
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....					
T. 7 Rivers.....	T. McKee.....	T. Menefee.....					
T. Queen.....685	T. Ellenburger.....	T. Point Lookout.....					
T. Grayburg.....2052	T. Gr. Wash.....	T. Mancos.....					
T. San Andres.....2500	T. Granite.....	T. Dakota.....					
T. Glorieta.....	T.	T. Morrison.....					
T. Drinkard.....	T.	T. Penn.....					
T. Tubbs.....	T.	T.					
T. Abo.....	T.	T.					
T. Penn.....	T.	T.					
T. Miss.....	T.	T.					

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	15	15	Soil and caliche	1140	1290	150	Anhydrite
15	170	155	Sandy Shale	1290	1310	20	Sandy Lime
170	195	25	Broken anhydrite	1310	1335	25	Anhydrite
195	210	15	Red Rock & anhydrite	1335	1350	15	Brown Lime
210	215	5	Anhydrite	1350	1375	25	Lime
215	230	15	Red Bed	1375	1400	25	Anhydrite & Lime
230	250	20	Blue Shale	1400	1675	275	Anhydrite
250	284	34	Red Beds	1675	1705	30	Red Sand
284	310	26	Anhydrite	1705	1720	15	Anhydrite
310	370	60	Anhydrite, Red Rock, Salt Stringers	1720	1730	10	Lime
370	375	5	Anhydrite, Red Bed	1730	1755	25	Anhydrite
375	390	15	Anhydrite & potash	1755	1790	35	Lime
390	395	5	Salt	1790	1805	15	Lime & anhydrite
395	406	11	Salt & anhydrite	1805	1832	27	Lime
406	430	24	Anhydrite	1832	1880	48	Anhydrite
430	435	5	Salt	1880	1889	9	Lime
435	450	15	Anhydrite & Salt	1889	1895	6	Sand
450	610	160	Salt & Polyhalite	1895	1905	10	Lime
610	635	25	Anhydrite & Dolomite	1905	1965	60	Anhydrite
635	1120	485	Anhydrite	1965	1985	20	Anhydrite & Lime
1120	1140	20	Anhydrite & Lime	1985	1995	10	Lime
				1995	2000	5	Anhydrite & Red Shale
2000	2025	25	Lime	2473	2643	170	Lime
2025	2039	14	Lime & Red Sand	2643	2655	11	Gray Lime
2039	2050	11	Gray Lime	2655	2687	32	Lime
2050	2065	15	Lime	2687	2699	12	Gray Lime
2065	2090	25	Gray Lime	2699	2768	69	Gray Lime
2090	2125	35	Lime	2768	2930	162	Lime
2125	2140	15	Gray Lime	2930	2945	15	Sand
2140	2180	40	Lime				
2180	2193	13	Sand				
2193	2218	25	Lime				
2218	2230	12	Gray Lime				
2230	2268	38	Lime				
2268	2281	13	Gray Lime				
2281	2299	18	White Lime				
2299	2379	80	Lime				
2379	2396	17	Lime & Sand				
2396	2415	19	Sandy Lime				
2415	2430	15	Pink Lime				
2430	2444	14	Lime				
2444	2461	17	Sandy Pink Lime				
2461	2473	12	Pink Lime				

