




AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE. If State Land submit 6 Copies

Malco Resler Yates State
(Company or Operator) (Lease)
Well No. 127, in NW 1/4 of NE 1/4 of Sec 3, T. 18, R. 28, NMPM.
Artesia Eddy County.
Well is 660 feet from North line and 1980 feet from East line
of Section 3. If State Land the Oil and Gas Lease No. is 647
Drilling Commenced January 15, 1956 Drilling was Completed January 28, 1956
Name of Drilling Contractor S. P. Yates Drilling Company
Address Artesia, New Mexico
Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until
, 19

OIL SANDS OR ZONES

No. 1, from 2370 to 2424 No. 4, from to
No. 2, from 2310 to 2325 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7	17	New	510				
4 1/2	9.5	New	2352			2310-25	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	7	510	100	Halliburton		
6 1/4	4 1/2	2352	100	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand oiled w/10,000 gallons lease crude mixed w/adonite and 20,000 lb. sand.

Result of Production Stimulation Well flowed 60 BOPD

Depth Cleaned Out 2424

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 2425 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing January 30, 1956

OIL WELL: The production during the first 24 hours was 60 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 37

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates 560	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen 1540	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres 2420	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	400		Red beds				
400	560		Anhydrite				
560	580		Red sand				
580	680		Anhydrite				
680	710		Red sand				
710	770		Anhydrite				
770	790		Red sand				
790	1540		Anhydrite				
1540	1580		Red sand				
1580	1840		Anhydrite				
1840	2050		Anhydrite and red sand				
2050	2270		Lime				
2270	2420		Lime and sand				
2420	2425		White dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

January 31, 1956

(Date)

Company or Operator Malco Dealer Yates

Address 304 Carper Bldg., Artesia, New Mexico

Name Lita P. Sheldon

Position or Title Sec. Oper. Comm.