NEW	MEXICO	OIL	CONSERVATION	COMMISSION
-----	--------	-----	--------------	------------

٠.

10

.

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Below

	11		
Notice of Intention to Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
NOTICE OF INTENTION TO PLUG WELL	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention to Squeeze	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	Notice of Intention (Other)	Notice of Intention (Other)	X
OIL CONSERVATION COMMISS Santa Fe, New Mexico	ION Artesia N. N. (Place)	Liair Ch (Date	<u>9, 1954</u>
Gentlemen:			
Following is a Notice of Intention	on to do certain work as described below at th	e	
ATTRICATE FRITE TCS C	CEP. (formerly Pueblo)	Well No 2	in
(Company or	Operator) 4, T18, R. 28		(Unit)
(40-acre Subdivision)	·····, <b>Τ</b> , <b>R</b> ,	NMPM.,	Pool
EDDY			
	ALL AND THE PARTY AND THE PART	NO DECLU ATIONS	
<ol> <li>At present well have</li> <li>Fropose to run new</li> <li>Pipe to be set at Hole will be bridg</li> <li>Eerove bridge and</li> </ol>	DLLOW INSTRUCTIONS IN THE RULES is 7" landed at 2172' with string 5t through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of bole. 2,000 gallons (or more) of own 5t".	n nc cement. 1 cement with 25 sks shot hole(at 2335') pay zone.	as possible.
<ol> <li>At present well have a set of the set of t</li></ol>	is 7" landed at 2172' with string 5t through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of bole. 2,000 gallons (or more) or	n nc cement. 1 cement with 25 sks shot hole(at 2335') pay zone.	as possible.
<ol> <li>At present well have a set of the set of t</li></ol>	is 7" landed at 2172' with string 5t through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of bole. 2,000 gallons (or more) or	n nc cement. 1 cement with 25 sks shot hole(at 2335') pay zone.	as possible.
<ol> <li>At present well ha</li> <li>Fropose to run new</li> <li>Pipe to be set at Hole will be bridg</li> <li>A.Remove bridge and</li> <li>Treat well with 12 Treatment to be do</li> </ol>	is 7" landed at 2172' with string 5½ through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of bole. 2,000 gallons (or more) of own 5½".	n nc cement. d cement with 25 sks shot hole(at 2335') pay zone. C jelled crude and s ALEFICAN ELIVELICS C	as possible.
<ol> <li>At present well ha</li> <li>Fropose to run new</li> <li>Pipe to be set at Hole will be bridg</li> <li>A.Remove bridge and</li> <li>Treat well with 12 Treatment to be do</li> </ol>	is 7" landed at 2172' with string 5t through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of bole. 2,000 gallons (or more) or	n nc cement. 1 cement with 25 sks shot hole(at 2335') pay zone.	as possible.
1.At present well ha 2.Fropose to run new 3.Pipe to be set at Hole will be bridg 4.Remove bridge and 5.Treat well with 12 Treatment to be do Approved.	ns 7" landed at 2172' with y string 5t through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of hole. 2,000 gallons (or more) of own 5t". By	n nc cement. d cement with 25 sks shot hole(at 2335') pay zone. f jelled crude and st <u>alter ICAN ELIVELICS C</u> <u>Company or Operator</u> <u>Automin</u> C.	as possible.
1.At present well ha 2.Fropose to run new 3.Pipe to be set at Hole will be bridg 4.Remove bridge and 5.Treat well with 12 Treatment to be do Approved.	<pre>ns 7" landed at 2172' with string 5½ through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of hole. 2,000 gallons (or more) of cwn 5½". </pre>	n nc cement. d cement with 25 sks shot hole(at 2335') pay zone. f jelled crude and st <u>alter ICAN ELIVELICS C</u> <u>Company or Operator</u> <u>Automin</u> C.	es possible. and. <u>UF.F.</u>
<pre>1.At present well ha 2.Fropose to run new 3.Pipe to be set at Hole will be bridg 4.Remove bridge and 5.Treat well with 12 Treatment to be do Approved</pre>	<pre>ns 7" landed at 2172' with string 5½ through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of hole. 2,000 gallons (or more) of cwn 5½". </pre>	n nc cement. d cement with 25 sks shot hole(at 2335') pay zone. f jelled crude and s ALEF ICAN ELIVERICS C Company or Operator C. Supt.	es possible. and. <u>UF.F.</u>
<pre>1.At present well ha 2.Fropose to run new 3.Pipe to be set at Hole will be bridg 4.Remove bridge and 5.Treat well with 12 Treatment to be do Approved</pre>	string 5t through 7" and 2320' or as near top of s ged to keep cement cut of clean bottom of hole. 2,000 gallons (or more) of own 5t". By By By	n nc cement. d cement with 25 sks shot hole(at 2335') pay zone. f jelled crude and s ALEF ICAN ELIVERICS C Company or Operator C. Supt.	as possible. and. <u>UFF.</u> <u>A. STAID</u> well to: FF.