


(Samples are in -)



County EDDY Depth 2400' Pool Artesia*

SCOUT REPORT
NEW MEXICO OIL CONSERVATION COMMISSION

Company G. Kelly Stout Well No. 1 Lease Humble St.

2310' Feet from S Line 330' Feet from E Line Sec. 4 Twp. 18 Rge. 28E

(2) Spl.

Land State Contractor Roach & Shepard.

T. A
T. X
B. X
T. Del.Li.
T. Del.Sd.
T. Y
T. SR
T. Q 2340 1500
T. GB
T. SA 2385
T. ~~SA~~ Livingston Sd. 2505
T. Blby
T. CF

Elevation 3658 Spudded 11-18-53 Completed 3-9-54

T. Tu. Total Depth 2526 P. B.
T. Full. Top Pay 2510 District 7
T. DR I. P. P 12 BOPD
T. Wich. Alb. Base BO 24 Hrs.
T. Abo Choke: Open Inch
T. WC Tubing 2 @ 2520 Ft.
T. Hu. Pressures: Tubing Casing
T. Per-Pe GOR Gravity 35
T. Penn. Effective Perforations
T. Strawn
T. Miss.

CSG. & CEMENTING REC'D

Size	Feet	Sax Cement
<u>8 1/2</u>	<u>505</u>	<u>50</u>

T. WF Acid & Shooting Record:
T. Dev. Hyd 3000 g From O.H. 2360 To 2392
T. Fuss. Hyd 1500 g From O.H. 2471 To 2516
T. Sil. From To
T. Mon. From To
T. Simp. From To
T. McK
T. Ell.
T. G.W.
T. Gr. SHOWS
T. S/FW 280-85
T. S/
T. S/
T. S/
T. S/
T. S/
T. S/

Nov. 18	Prep to spud	✓
Nov 24	<u>TD 505 anchy</u>	✓ ✓
	<u>WOC</u>	✓
	<u>d 1401 anchy</u>	<u>→ 2526 li. installing</u>
	<u>d 2065 li.</u>	<u>td</u>
	<u>d 2406 li.</u>	<u>TD 2526 li. installing</u>
	<u>TD 2518 li.</u>	<u>2471-2516</u>
	<u>Sdo</u>	<u>Hyd 1500 2512-18</u>
		<u>Hyd. 3000 2360-92</u>

TD 2526 line, installing intermitter
✓

TD 2526 li Reperump. + tanks
✓

T.D. 2526 li Istg. on pump, pump 128024'
✓

Completed well.