

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

June 12, 1961

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Pan American Petroleum Corporation

State OK Well No. 1 in 0
 (Company or Operator) T. 18-S R. 28-S NMPM, Empire Abo Pool
 SW 1/4 SE 1/4 of Sec. 6, T. 18-S, R. 28-S, NMPM, Empire Abo Pool
 (40-acre Subdivision) County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Subsequent to G-103 approved 5-11-61, load was never recovered from perforations 6356'-72'. Set GI Bridge Plug at 6350' and squeezed perforations 6356'-72' with 75 sx. cement. Perforated 6334'-44' with 2 SPT, acidized with 2000 gals. LSTHE acid. No trace of oil or gas. Plugged perforations 6334'-44' w/gal seal. Perforated 6312'-20', 6324'-27' w/2 SPT, acidized w/2000 gal LSTHE. No trace of oil or gas. Re-fractured with 40,000 gallons gelled water containing 1/2" sand/gal. Lack 995 barrels of load to recover. All possibilities exhausted. It is proposed to PIA well as follows: Spot 20 sx. cement plug from 6250'-6390', cut and pull casing from approximately 5350', spot 25 sx plug half in and half out of 4-1/2" casing stub, spot 30 sx. from 3870'-3970', 30 sx from 2205'-2305', 25 sx half in and out of 8-5/8" casing at 877', 10 sx plug at surface. All intervals filled with heavy mud laden fluid. Erect steel PIA marker, restore ground to natural contour.

Approved JUN 15 1961, 19____
Except as follows:

Pan American Petroleum Corporation

Original Signed by Company or Operator

By V. E. STALEYPosition Area Superintendent

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSIONBy W. A. GussertTitle OIL AND GAS INSPECTORName V. E. StaleyAddress Box 68, Hobbs, New Mexico

OIL CONSERVATION COMMISSION		
ARTESIA DISTRICT OFFICE		
No. Copies Received		
DISTRIBUTION		
	NO. FURNISHED	
OPERATOR		
SANTA FE		
PRORATION OFFICE		
STATE LAND OFFICE		
U. S. G. S.		
TRANSPORTER		
FILE		
BUREAU OF MINES		