YATES PETROLEUM CORPORATION Ballard A #1 Section1-T18S-R29E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

clean. POOH with bit. Shut well in. 4-25-2000 - RIH with bit and tagged up at 1384'. Rigged up swivel. Cleaned out to 2205'. Circulated hole clean. POOH with bit. Shut well in. 4-26-2000 - TIH with bit and tagged fill at 2205'. Rigged up swivel. Cleaned out to 2650'. Circulated hole clean. POOH with bit. Rigged down and moved out reverse unit equipment. TIH with tubing to 2650'. Moved in and rigged up cement equipment. POOH with 20 joints tubing. Shut well in. 4-27-2000 - TIH with tubing to 2646'. Spotted 30 sacks Class C Neat cement. POOH with 40 joints tubing. WOC 4 hours. RIH with tubing and tagged plug at 2615'. Spotted 30 sacks

40 joints tubing. WOC 4 hours. RIH with tubing and tagged plug at 2615'. Spotted 30 sacks Class C cement. POOH with 40 joints tubing. WOC 2 hours. RIH with tubing and tagged plug at 2445'. Circulated hole with mud laden fluid. POOH to 1102'. Spotted 75 sacks Class C Neat cement. POOH with tubing. WOC. Shut well in.

4-29-2000 - RIH with tubing and tagged plug at 104'. POOH with tubing. Rigged down tubing equipment and floor. Nippled down BOP. Nippled up wellhead. Circulated 70 sacks Class C Neat cement down 7" casing up to surface 8-5/8" casing and backside of 8-5/8" casing. Shut well in.

5-2-2000 - Tagged plug at 6' down. Nippled down wellhead. Rigged down pulling unit. Installed regulation abandonment marker. PLUGGED AND ABANDONED - FINAL REPORT.

Rust

Rust# Klein ' Operations Technician October 2, 2000