Form 3160-5 (August 1999)

unit.

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

5. Lease Serial No. SUNDRY NOTICES AND REPORTS ON WELLS LC-051102A Do not use this form for proposals to drill or to re-enter an 6. If Indian, Allottee or Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side 1. Type of Well 8. Well Name and No. 🗓 Oil Well 🔲 Gas Well 🔲 Other Ballard A #2 Name of Operator Yates Petroleum Corporation 9. API Well No. 3b. Phone No. (include area code) 30-015-03238 10. Field and Pool, or Exploratory Area 505-748-1471 105 S. 4th St. - Artesia, NM 88210 Location of Well (Footage, Sec., T., R., M., or Survey Description) oco Hills-Queen-GB-SA 11. County or Parish, State 2310' FSL & 2310' FEL of Section 1-T18S-R29E (Unit J, NWSE) Eddy Co., NM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Production (Start/Resume) ■ Water Shut-Off Deepen Deepen Acidize Well Integrity Notice of Intent ☐ Reclamation ☐ Alter Casing Fracture Treat **New Construction** ☐ Recomplete Other Casing Repair Subsequent Report ☐ Temporarily Abandon Plug and Abandon ☐ Change Plans Water Disposal Final Abandonment Notice Plug Back Convert to Injection Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 2-2-2000 - Moved in and rigged up pulling unit and plugging equipment. Dug out cellar. Nippled down wellhead and nippled up BOP. Rigged up floor and 2-7/8" tubing equipment. Shut well in. 2-3-2000 - Rigged up wireline. TIH with gauge ring to 2585'. POOH with gauge ring. TIH with CIBP and set CIBP at 2585'. TOOH w/tools. Rigged down wireline. Rigged down tubing equipment and floor. Nippled down BOP and nippled up wellhead. Rigged down pulling unit and plugging equipment. Shut down till further notice. 3-30-2000 - Moved in and rigged up coiled tubing unit. Rigged up wireline. Attempted to remove 7" swedge. Casing broke off 4' below surface above bell nipple. Casing seems to be collapsed below bell nipple. Could not TIH. Rigged down wireline and coiled tubing

Spotted a 30 sacks Class C cement plug. POOH with coiled tubing. TIH with wireline.

14. I hereby certify that the foregoing is true and correct CONTINUED ON NEXT PAGE:

Name (Printed/Typed)

Rusty Klein

Signature

Date Jan. 30, 2001

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

3-31-2000 - Rigged up coiled tubing unit and wireline. TIH with CIBP on wireline and set CIBP at 2590'. POOH with wireline. TIH with coiled tubing and tagged CIBP at 2590'.

Approved by Recard

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Date

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

YATES PETROLEUM CORPORATION Ballard A #2 Section 1-T18S-R29E Eddy County, New Mexico

## SUNDRY NOTICE CONTINUED:

Perforated 6 holes at 1125'. TOOH. TIH with wireline. Perforated 6 holes at 950'. TOOH. TIH with cement retainer on wireline and set retainer at 1000'. TIH coiled tubing. Sting into retainer. Established injection rate. Squeezed with 75 sacks Class C, leaving 35' of cement on top of retainer. POOH with coiled tubing. TIH with cement retainer on wireline and set retainer at 300'. POOH with wireline. TIH with coiled tubing. Sting into cement retainer. Squeezed with 60 sacks Class C cement, leaving 35' of cement on top of cement retainer. Pulled up hole with coiled tubing. Spotted 15 sacks Class C cement from 50' to surface. TOOH with coiled tubing. Rigged down plugging equipment. Installed regulation abandonment marker. PLUGGED AND ABANDONED - FINAL REPORT. Plugging completed 3-30-2000.

Rusty Klein

Operations Technician January 30, 2001