

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.LC 051102 (b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> WIW - P4A	NW OIL CONS. COMMISSION	7. UNIT AGREEMENT NAME	Loco Hills Flood
2. NAME OF OPERATOR Yates Pet. Corp.	Drawer DD	8. FARM OR LEASE NAME	Ballard "B"
Newmont Oil Company	Artesia, NM 88210	9. WELL NO.	No. 3
3. ADDRESS OF OPERATOR		10. FIELD AND POOL, OR WILDCAT	Loco Hills (Q.G.SA)
P. O. Box 1305, Artesia, N.M.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	Sec. 1-18-29
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface		12. COUNTY OR PARISH	Eddy
330' FNL 990' FEL	Sec. 1-18-29	13. STATE	N.M.
14. PERMIT NO.	15. ELEVATIONS (Show whether at surface, etc.)		
	3542' GL		

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/28/83----Rigged up, pulled 73 jts 2 3/8" tbg and SN. Left packer in hole. Ran 2 3/8" tbg open ended to 2750' and spotted 100 sacks cement w/2% CalCl. Pulled tbg and shut down.

10/29/83...Tagged plug at 2300'. Mudded up, checking hole in csg. Hole in csg between 500 and 625'. Perf base of salt at 1127'. Ran packer to 750' and squeezed 50 sacks cement w/2% CalCl. at 1000' psi. WOC.

11/1/83...Pressured up on csg to 500 psi. Okay. Tagged plug at 975', perf top of salt at 418'. Squeezed 50 sks cmt. WOC.

11/1/83....Pressure up on csg to 500 psi. Okay. Tagged plug at 975'. Perf top of salt at 418'. Squeezed 50 sks cmt. WOC.

11/2/83...No plug. Spotted 50 sks cement at 625'. SI WOC. Tagged plug at 418'. Could not pressure up on csg. Re-spotted 25 sacks at 413'. SI WOC.

11/3/83...Tagged plug at 380'. Pressure tested csg to 500 psi. Okay. Pumped 20 sacks between 8" and 7" csg. Spotted 70 sacks at 380'. Set 15 sack cement plug and dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

E. Robert Lisdale

TITLE

Engineer

DATE

4/22/85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

9-23-86

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Post ID-2
4-26-85
P4A