Form 9-881 a	N. M. O. C. C, COPY. N. M. O. C. C, COPY. Approval expires 12-31-60.
(Feb. 1951)	(SUBMIT IN TRIPLICATE) Land Office Las Grue
PPROVED	UNITED STATES
DEPA	RTMENT OF THE INTERIOR Unit RECEIV
KNAUF	GEOLOGICAL SURVEY
JAMES THE MERCE	DEC 1 9 19
SUNDRY NOTIO	CES AND REPORTS ON WELLSO, C. C.
	ARTESIA. DET
NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF. NOTICE OF INTENTION TO RE-DRILL OR REPAIR W	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY	CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	August 25, 19.
Western Development	
Wall No Killer 1 is located 198	0 ft. from $\left\{ \begin{array}{c} N \\ S \end{array} \right\}$ line and 1980 ft. from $\left\{ \begin{array}{c} W \\ W \end{array} \right\}$ line of sec4
Loco Hills	
The elevation of the derrick floor abo	ve sea level is <u></u>
The elevation of the derrick floor abo	ve sea level is <u>3539</u> ft. DETAILS OF WORK
(State names of and expected depths to objective sar	
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Commented from 2848 ' (T.D. 875', set 50' coment plug 825' to 360'. set 50' coment	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme nts, and all other important proposed work)
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Commented from 2848 ' (T.D. 875', set 50' coment plug 825' to 360'. set 50' coment	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, com- nits, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax.
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, community, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, com- nits, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax.
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, community, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re Location is clean and read	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cements, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.
(State names of and expected depths to objective sar ing point Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re Location is clean and read	DETAILS OF WORK nds: show sizes, weights, and lengths of proposed casings; indicate mudding jobs, commis, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.
(State names of and expected depths to objective saming point Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re Location is clean and read	DETAILS OF WORK nds; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, community, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.
(State names of and expected depths to objective sar Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cament plug 825' to 360', set 50' cement to surface and cemented re Location is clean and read I understand that this plan of work must receive Company <u>C. E. Roach Drilli</u> Address <u>102 South Second S</u>	DETAILS OF WORK nds: show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comm nts, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.
(State names of and expected depths to objective sar Pulled 336' 8 5/8" casing. Cemented from 2848 ' (T.D. 875', set 50' cement plug 825' to 360', set 50' cement to surface and cemented re Location is clean and read I understand that this plan of work must receive Company <u>C. E. Roach Drilli</u>	DETAILS OF WORK nds: show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comm nts, and all other important proposed work)) to 2775' with 25 Sax and mudded from 2775' to from 875' to 825' with 15 sax and mudded from nt plug from 360' to 310' with 15 sax and mudded gulation marker with 5 sax. y for inspection.