	N. M. O. C. C. DOPY	
		Budget Bureau No. 42-R358.4. Approval expires 12-31-60.
(Feb. 1951) (Feb.		Land Office
TOROV ((SUBMIT IN TRIPLICATE)	Lease No. 058579
Pres	UNITED STATES	Color.
DEPAR	TMENT OF THE INTERIOR	Unit RECEYVED
MAN CHOOK	GEOLOGICAL SURVEY	100 · ~ D
DONNIE EIGINEEN		APR 1 1962
CTING DISTRICT		·>03
CUNDRY NOTIC	ES AND REPORTS OF	WEITRES C. C.
SUNDRI NOTIC	ES AND REFORTS OF	WELLO-SIA, OFFICE
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATEL	R SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		ING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WEL		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTOR	
NOTICE OF INTENTION TO ABANDON WELL	t reating	X X X X Y Y E BARK
(INDICATE ABOVE BY CH	HECK MARK NATURE OF REPORT, NOTICE, OR OTHE	
		-
		March 26 , 19.63
Banner Miller		
	ft. from $\left\{ \begin{matrix} N \\ X \end{matrix} \right\}$ line and 2310 ft. fr	rom $\left\{ \frac{1}{1} \right\}$ line of sec. 5
/ CII 1 10, 15 IOCALCU	BA Inte und the fit in	[W] 0. 000
E/4 NW/4 5	- <u>\$ 29-E NMPM</u>	
(¼ Sec. and Sec. No.) (Twp.)) (Range) (Meridian)	Now Marico
Laco Hills (Field)	(County or Subdivision)	(State or Territory)
1 a averal		
The elevation of the derrick floor abov		
he elevation of the derrick floor abov	ve sea level is 3562 ft. DETAILS OF WORK	asings; indicate mudding jobs, cement-
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed c ts, and all other important proposed work)	
he elevation of the derrick floor abov	ve sea level is 3563 ft. DETAILS OF WORK ds; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total depth of cable tools. Ran Gamma F	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point the subject well was cleaned on new total depth of 2762' with gs. Ran Lynes straddle pack follows:	ve sea level is 3562 ft. DETAILS OF WORK ds; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total depth of cable tools. Ran Gamma R ters on 2 7/8 ¹⁴ OD tubing an	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point as subject well was cleaned of new total depth of 2762' with gs. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand	ve sea level is 3562 ft. DETAILS OF WORK ds; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total depth of cable tools. Ran Gamma H ters on 2 7/8 ¹⁰ OD tubing an and 481 barrels fresh water 4 and 507 barrels fresh water	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at 2400-72' - 20,000 lb. sand at	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tabing an and 481 barrels fresh water d and 507 barrels fresh water	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point as subject well was cleaned of new total depth of 2762' with gs. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tabing an and 481 barrels fresh water d and 507 barrels fresh water	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at 2400-72' - 20,000 lb. sand at	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tabing an and 481 barrels fresh water d and 507 barrels fresh water	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at 2400-72' - 20,000 lb. sand at	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tabing an and 481 barrels fresh water d and 507 barrels fresh water	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor abov State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at 2400-72' - 20,000 lb. sand at	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed c ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tabing an and 481 barrels fresh water d and 507 barrels fresh water	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor above State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand an 2480-2552' - 15,000 lb. sand and 2400-72' - 20,000 lb. sand and Cleaned out to total depth and	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tabing an and 481 barrels fresh water d and 507 barrels fresh water d and 499 barrels fresh water d returned well to producing	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
Tunderstand that this plan of work must receive	Are sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tubing an and 481 barrels fresh water and 507 barrels fresh water and 499 barrels fresh water a returned well to producing approval in writing by the Geological Survey bef	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv
The elevation of the derrick floor above State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2710-62' - 15,000 lb. sand an 2480-2552' - 15,000 lb. sand and 2400-72' - 20,000 lb. sand and Cleaned out to total depth and	Are sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) ut to original total dopth of cable tools. Ran Gaunna H ters on 2 7/8 ¹⁴ OD tubing an and 481 barrels fresh water and 507 barrels fresh water and 499 barrels fresh water a returned well to producing approval in writing by the Geological Survey bef	2720', drilled deeper to Lay-Neutron and Caliper d treated open hole interv er. status.
The elevation of the derrick floor above State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with gs. Ran Lynes straddle pack follows: 2718-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at Cleaned out to total depth and I understand that this plan of work must receive Company International Oil & G	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) we to original total depth of cable tools. Ran Gamma H ters on 2 7/8 ⁴ OD tubing an and 481 barrels fresh water d and 507 barrels fresh water d and 507 barrels fresh water d returned well to producing approval in writing by the Geological Survey bef is Corporation	2720', drilled deeper to Lay-Neutron and Caliper d treated open hole interv er. status. Ptr MAR Status ore operations may be corfiguence.
Tunderstand that this plan of work must receive	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) we to original total depth of cable tools. Ran Gamma H ters on 2 7/8 ⁴ OD tubing an and 481 barrels fresh water d and 507 barrels fresh water d and 507 barrels fresh water d returned well to producing approval in writing by the Geological Survey bef is Corporation	2720', drilled deeper to kay-Neutron and Caliper d treated open hole interv er. status. Ptr MAR Status ore operations may be corfiguence.
The elevation of the derrick floor aboves the elevation of the derrick floor aboves the subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2718-62' - 15,000 lb. sand an 2480-2552' - 15,000 lb. sand and 2480-2552' - 15,000 lb. sand and 2480-2552' - 20,000 lb. sand and Cleaned out to total depth and I understand that this plan of work must receive Company International Oil & G Address P.O. Box 427	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) we to original total depth of cable tools. Ran Gamma H ters on 2 7/8 ⁴ OD tubing an and 481 barrels fresh water d and 507 barrels fresh water d and 507 barrels fresh water d returned well to producing approval in writing by the Geological Survey bef is Corporation	2720', drilled deeper to kay-Neutron and Caliper d treated open hole interv er. status. Ptr MAR Status ore operations may be corfiguence.
The elevation of the derrick floor above State names of and expected depths to objective sand ing point as subject well was cleaned on new total depth of 2762' with gs. Ran Lynes straddle pack follows: 2718-62' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at 2480-2552' - 15,000 lb. sand at Cleaned out to total depth and I understand that this plan of work must receive Company International Oil & G	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) we to original total depth of cable tools. Ran Gamma H ters on 2 7/8 ⁴ OD tubing an and 481 barrels fresh water d and 507 barrels fresh water d and 507 barrels fresh water d returned well to producing approval in writing by the Geological Survey bef is Corporation	2720', drilled deeper to kay-Neutron and Caliper d treated open hole interv er. status. Ptr MAR Status ore operations may be corfiguence.
The elevation of the derrick floor aboves the elevation of the derrick floor aboves the subject well was cleaned on new total depth of 2762' with s. Ran Lynes straddle pack follows: 2718-62' - 15,000 lb. sand an 2480-2552' - 15,000 lb. sand and 2480-2552' - 15,000 lb. sand and 2480-2552' - 20,000 lb. sand and Cleaned out to total depth and I understand that this plan of work must receive Company International Oil & G Address P.O. Box 427	ve sea level is 3562 ft. DETAILS OF WORK da; show sizes, weights, and lengths of proposed of ts, and all other important proposed work) we to original total depth of cable tools. Ran Gamma H ters on 2 7/8 ⁴ OD tubing an and 481 barrels fresh water d and 507 barrels fresh water d and 507 barrels fresh water d returned well to producing approval in writing by the Geological Survey bef is Corporation	2720°, drilled deeper to Lay-Neutron and Caliper d treated open hole interv

NEW MEXICO OIL CONSERVATION COMMISSION P. O. DRAWER DD TENTH & DALLAS STREETS ARTESIA, NEW MEXICO

April, 1963

No. A 26

SUPPLEMENT TO THE OIL PRORATION SCHEDULE

DATE April 1, 1963

PURPOSE: ALLOWABLE REVISION (SECOND MONTH)

Effective April 1, 1963, the allowable of the International Oil & Gas Corp., Banner Miller, Well #3 C, 5-18-29, Loco Hills Pool, is hereby increased from 3 barrels daily to 36 barrels daily or a total of 1080 barrels for the month.

OIL CONSERVATION COMMISSION

SUPERVISOR, DISTRICT NO.

MLA/uh

International Oil & Gas Corp.

Texas-New Mexico

EXTRA COPY

·