



NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

G B & C E Suppes
Miller Company or Operator
Well No. 5 in SE-NE-NE of Sec. 6, T. 18S
Lease R. 29E, N. M. P. M. Loco Hills Field, Eddy County.
Well is 990 feet south of the North line and 330 feet west of the East line of Sec 6
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is. Address.
If Government land the permittee is. Address.
The Lessee is. Address.
Drilling commenced Jan 21 19 50 Drilling was completed Feb 28 19 50
Name of drilling contractor Company tools Address.
Elevation above sea level at top of casing 3589 feet.
The information given is to be kept confidential until 19.

OIL SANDS OR ZONES
No. 1, from 2520 to 2536 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS
Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	28	8	used	345	Tex	160			Plugged well

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
10	8 5/8	345	50	Plug & pres		10 sacks aquagel

PLUGS AND ADAPTERS
Heaving plug—Material Length Depth Set
Adapters — Material Size

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS
If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED
Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 3031 feet, and from feet to feet

PRODUCTION
Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES
Clyde Galloway Driller E I Glover Driller
H T Flynn Driller Max Stephens Driller

FORMATION RECORD ON OTHER SIDE
I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 20 day of March 19 50
Notary Public
Mv Commission expires 4-24-52
Artesia New Mex 3-20-50
Name B E Kennedy Partner
Position
Representing G B & C E Suppes Company or Operator
Address Tulsa Okla

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	135	135	Caliche
135	260	125	Red Rock
260	280	20	Anhydrite
280	295	15	Red Rock
295	692	397	Salt
692	870	178	Anhydrite
870	885	15	Salt
885	1930	1045	Anhydrite
1930	1945	15	Red Sand
1945	2267	322	Anhydrite
2267	2520	253	Lime
2520	2536	16	Sand
2536	2650	114	Lime
2650	2668	18	Pink Lime
2668	2710	42	Lime
2710	2842	132	White Lime
2842	3031	189	Gray Lime