

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC - 061701

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER **X - Water Injection Well**

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255 O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface990' FS & WLS Sec. 8, T18S, R29E
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Not Available

7. UNIT AGREEMENT NAME

Ballard Grayburg
San Andres Unit

8. FARM OR LEASE NAME

Tract No. 14

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Loco Hills Queen
Grayburg San Andres11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

8 - 18S - 29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Cement Squeeze Liner Top X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths and zones pertinent to this work.)*

1. Rigged up pulling unit, pulled tubing and injection packer.

2. Ran 5 1/2" retrievable Bridge Plug and set @ 2204'.

3. Ran 7" squeeze packer and set @ 1950'.

4. Established pump-in rate of 3 BPM @ 1000 psi.

5. Cement squeezed with 250 sx Class H w/.3 of 1% HSL-249 (WL material) & 6# salt/sx.
Maximum squeeze pressure - 2 BPM @ 1050 psi.

6. Drilled out cement from 1988' to top of liner (2161').

7. Drilled 5' cement out of top of liner and retrieved B. P.

8. Hydrotested 5 1/2" Johnston tension packer on 2-3/8" SALTA tubing in hole.

9. Loaded and circulated backside with chemical water and set packer @ 2811'.

10. Returned well to injection.

Note: Prior water-flow from behind liner was effectively shut off.

18. I hereby certify that the foregoing is true and correct

SIGNED

Original Signed by
Jerry E. Buckles

TITLE

Area Supervisor

DATE

August 9, 1979

(This space for Federal or State office use)

APPROVED BY

ALBERT R. STALL

TITLE

ACTING DISTRICT ENGINEER

DATE

AUG 13 1979

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones; or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.