at at	DEPART O	N11.1X	and Office Las Cruces		
	(SUBMIT	IN TRIPLICATE)	Lenso No. LC-058603		
the second s	UNIT	ED STATES	₩-11 o m		
		OF THE INTERI			
. I come and the second s	GEOLO	GICAL SURVEY			
	01010				
SUNDRY 1	NOTICES A	ND REPORTS			
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT O	F WATER SHUT-OFF		
NOTICE OF INTENTION TO CHANGE PL	AN5	SUBSEQUENT REPORT O	F SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATE	R SHUT-OFF	SUBSEQUENT REPORT O	OF ALTERING CASING		
NOTICE OF INTENTION TO RE-DRILL O	R REPAIR WELL	SUBSEQUENT ACTONY V	OF REDRILLING OR REPAIR		
NOTICE OF INTENTION TO SHOOT OR	ACIDIZE	SUBSEQUENT REFORT	HISTORY		
NOTICE OF INTENTION TO PULL OR A	LTER CASING	SUPPLEMENTARY WELL	HISTORY		
NOTICE OF INTENTION TO ABANDON	WELL	A			
		K NATURE OF REPORT, NOTICE,	OR OTHER DATA)		
(INDICAT	E ABOVE BY CHECK MAR				
		Sept.			
Well No is loo	cated <u>660</u> ft. f	rom [N] line and 462	$\frac{E}{W}$ ft. from $\frac{E}{W}$ line of sec. 8		
			(Meridian)		
NK1 OF NW1 (14 Sec. and Sec. No.)	(Twp.)	(Range)	Nor Mexico		
Loco Hills		Dicy	(State or Territory)		
(Field)	(Cour	ty or Subdivision)			
The elevation of the derric	The elevation of the derrick floor above sea level is <u>3556</u> ft.				
	DET	AILS OF WORK			
dentha	to objective sands; show	sizes, weights, and lengths of p	proposed casings; indicate mudding jobs, coment- vork)		
(State names of and expected depths	ing points, and	ill other important proposed -	, it may alward back to		
This well was drille	ai to 3017 ft.	in 1939 and at t year, the open h	he time was plugged back to whe became bridged at 2660 depth. There is 60 fect of		
2000. During re-nor	nked with wash	pipe above this	depth. There is by rect of		
tubing and wash pip	e in the old s	shot hole from 255	to 2650. He plan to plug		
the well in Oct. of	1952 by place	ing a cement plug	at 2000 leet. After mad, no		
2635. During re-work efforts this year, the open hole became blidged to wood and the hole was junked with wash pipe above this depth. There is 60 feet of tubing and wash pipe in the old shot hole from 2550 to 2630. We plan to plug tubing and wash pipe in the old shot hole from 2500 to 2630. We plan to plug the well in Oct. of 1952 by placing a cement plug at 2300 feet. After that, we will attempt to recover the 7" casing above 2300 feet and the 8" casing above will attempt to recover the 7" casing above 2500 feet and the 8" casing above					
500 feet. We would then place central place uning surface sine and at the					
300 feet. We would then place cement plugs in the open hole up and at the the salt beds (700'), in the top of the remaining surface pipe and at the the salt beds (700').					
the salt beds (700'), in the top of the remaining sufface pupe the now would ground level point of the well. The existing casing and open hole now would					
pround level point of the well. The darphing the first time.					

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.				
Company_	Yancey-Harris Co			
Address	1230 Mercantile Bank Bldg.	By John A. Avers		
	Dallas, Texas	By John A. Hyers		
		Title Agent of Company		
	U. S. GOVERNMENT PRINTING OFFICE	16-8437-4		