

FORMATION RECORD

| FROM | TO | THICKNESS IN FEET | FORMATION |
|--|-----------------|----------------------|---|
| 0 | 35 | 35 | Gyp |
| 35 | 90 | | Red Rock |
| 90 | 100 | | Anhyd. |
| 100 | 140 | | " |
| 140 | 190 | | Red Sand |
| 190 | 215 | | Red Beds |
| 215 | 280 | | Red Rock |
| 280 | 295 | | Anhyd. |
| 295 | 305 | | Red Rock |
| 305 | 315 | | Salt (From 321 ft 8 1/2") |
| 315 | 320 | | Salt |
| 320 | 350 | | " |
| 350 | 425 | | " |
| 425 | 500 | | " |
| 500 | 575 | | " |
| 575 | 615 | | " |
| 615 | 680 | | " |
| 680 | 740 | | " |
| 740 | 770 | | " |
| 770 | 800 | | Anhyd. |
| 800 | 900 | | " |
| 900 | 1005 | | " |
| 1005 | 1595 | | " |
| 1595 | 1630 | | Anhyd. & lime |
| 1630 | 1660 | | Anhyd. |
| 1660 | 2000 | | " |
| 2000 | 2015 | | Red Sand |
| 2015 | 2075 | | Anhyd. & lime |
| 2075 | 2125 | | Anhyd. |
| 2125 | 2140 | | Red Sand (Corrected from 2140 to 2125) |
| 2222 | 2222 | | xxxxxxx |
| 2250 | 2275 | | Anhyd. |
| 2275 | 2290 | | Gray Lime |
| 2290 | 2305 | | Anhyd & red shale |
| 2305 | 2318 | | Lime |
| (2318 running and cementing 7" OD with 100 lbs cement & 1/2 aquagel) (Drilled 15 ft cement) | | | |
| 2318 | 2340 | | Lime |
| 2340 | 2345 | | Anhyd & lime |
| 2345 | 2350 | | Anhyd & lime shale |
| 2347 | 2353 | | Lime |
| 2353 | 2425 | | " |
| 2435 | 2452 | | Sand (SO 2435 to 2441) 2441 to '52 oil in hole |
| 2452 | 2474 | | Lime |
| 2474 | 2483 | | Gray Lime |
| 2483 | 2542 | | Lime |
| 2542 | 2553 | | Gray Lime |
| 2553 | 2585 | | Lime |
| 2585 | 2596 | | Sandy Lime |
| 2596 | 2607 | | Brown lime |
| 2607 | 2613 | | Gray lime |
| 2613 | 2627 | | Lime |
| 2633 | 2641 | | Sandy lime |
| 2641 | 2725 | | Lime (Total Depth) |
| Plugged back to 2465 for shot | | | |